



# Twofold faceplate, horizontal 71 mm centre distance, for two single switch functions, Niko Rocker alu gold brushed

**227-56801**



The Niko Rocker twofold horizontally oriented faceplate clicks onto two single switch functions that have been vertically installed on top of each other with a centre distance of 71 mm. The faceplate combines with any available Niko Rocker single switch function. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is made of aluminium. The lower frame is made of white, gold coated polycarbonate (PC) + acrylic-styrene-acrylate (ASA). The upper frame is 6 mm thick and the lower frame 2 mm.



Niko recommends a design combination with a finishing set in the following colour: alu gold.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)

## Technical data

Twofold faceplate, horizontal 71 mm centre distance, for two single switch functions, Niko Rocker alu gold brushed.

- Double faceplate for two switches.
- Colour faceplate: alu gold brushed
- Colour RAL (approximately): 1000
- Colour NCS (approximately): NCS S 3020-Y
- Recommended colour central plate: alu gold
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material finishing: The upper frame is made of aluminium. The lower frame is made of white, gold coated polycarbonate (PC) + acrylic-styrene-acrylate (ASA).
- Surface treatment: anodised
- Surface finishing: matt
- Coating lower frame: enamelled gold

- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Recess for indication led:
  - the faceplate is fitted with a light guide
  - the light guide is made of a translucent plastic
  - the light guide transports the light from the optional LED to the lever
  - please note that the faceplate should not be mounted upside down to ensure that the optional LED fits nicely with the light guide
- Surface-mounting height: max. 8.5 mm
- Halogen-free: yes
- Fire safety:
  - self-extinguishing: complies with a filament test of 650°C
- Centre-to-centre distance: 71 mm
- Protection degree: the combination of a mechanism, a central plate and a faceplate has a protection degree of IP20D
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 mm x 154 mm x 13 mm
- Dimensions visible (HxWxD): 83 mm x 154 mm
- Marking: EU