

## Data Sheet | Item Number: 733-191

Operating tool; made of insulating material; 1-way; loose; yellow

<https://www.wago.com/733-191>



Color: ■ yellow

### Technical data

Number of spacings	1 -times
--------------------	----------

### Physical data

Depth	18.75 mm / 0.74 inches
Pin spacing	2.5 mm

### Mechanical data

Suitable	for male and female connectors with CAGE CLAMP® connection
----------	--

### Material data

Color	yellow
Material group	I
Insulation material (main housing)	Glass fiber-reinforced polyamide (PA66 GF)
Flammability class per UL94	HB
Fire load	0.006 MJ
Weight	0.2 g

### Commercial data

Product Group	3 (Multi Conn. System)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454830069
Customs tariff number	82055980000

**Product Classification**

UNSPSC	27112809
eCl@ss 10.0	27-44-04-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 10.0	EC002848
ECCN	NO US CLASSIFICATION

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Approvals / Certificates**

**Approvals for marine applications**



Approval	Standard	Certificate Name
LR Lloyds Register	IEC 61984	96/20035 (E5)

**Downloads**

**Environmental Product Compliance**


Compliance Search
Environmental Product Compliance 733-191 

**CAD/CAE-Data**

CAD data
2D/3D Models 733-191 

CAE data
ZUKEN Portal 733-191 

**Installation Notes**



Conductor termination via operating tool (733-191)

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: [www.wago.com](http://www.wago.com)