

## 26P-26Z05: Press swivel adapter 26x3/4"



### Commercial information

The body of the fitting is made from CW617N brass. These fittings offer great advantages with regard to corrosion and they are also better for the environment.

- The fitting has a buffer ring that prevents direct galvanic contact between the aluminium of the pipe and the brass of the fitting.
- This excludes the possibility of electrolysis occurring.
- The fitting is equipped with O-rings made from EPDM and RVS pressure sleeves with 3 inspection windows.
- In order to prevent assembly errors, the dimensions and type of press profile which can be pressed are shown on the RVS sleeves

### Basic unit dimensions

Height	34 mm
Length	58 mm
Width	34 mm
Net weight	0.119 kg

### Certificates

KIWA, KOMO, DVGW Wasser, ATG, ÖN EN 21003-2/-3, ÖVGW Wasser, ETA, STF, QB (CSTBat), AFNOR, ACS, WRAS, GOST-R, PZH, ITC, TSU, DNV-GL, EMI

### Applications

Potable water, Heating, Compressed air, Cooling, Sanitary

### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Outer pipe diameter connection 1	26 Millimetre
Surface protection connection 1	Nickel-plated	Length	58 Millimetre
Material connection 2	Brass	Length of connection 1	28.5 Millimetre
Material quality connection 2	CuZn40Pb2 (CW617N)	Working length connection 1	28.5 Millimetre
Surface protection connection 2	Nickel-plated	Length of connection 2	20.5 Millimetre
Shape	Straight	Working length connection 2	19 Millimetre
Reducing	✘	Wrench width	0 Millimetre
Eccentric	✘	Wrench width union nut	0 Millimetre
System specific	✓	Medium temperature (continuous)	-10 70 Degrees celsius
Connection 1	Press sleeve	Max. operating pressure at 20 °C	10 Bar
Contour code connection 1	TH	Standard Dimension Ratio (SDR)	0
Nominal diameter connection 2	3/4 inch (20)		
Connection 2	Union nut		
Main colour fitting	Brass		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
High tensile strength	✘		
With thermal insulation	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✘		
KOMO certified	✓		
Type approval according to BBR/EKS	✘		