



Color: ■ black

Power supply is performed via 10 inline splicing connectors with levers 221-2411.  
 Application example: blind drives control

Includes: one cable clamp and two mounting screws

### Electrical data

#### Ratings per IEC/EN

Nominal voltage (III/3)	400 V
Rated impulse withstand voltage (III / 3)	6 kV
Rated current	16 A

#### Ratings per IEC/EN 2

Rated voltage (III / 3)	250 V
Rated impulse withstand voltage (III/3)	4 kV

### Connection Data

#### Connection 1

Connection type	Input
-----------------	-------

#### Connection 2

Connection type	Output
Connector	MIDI socket, 4-pole (770-204)

### Physical data

Width	190 mm / 7.48 inches
Height	31 mm / 1.22 inches
Depth	145 mm / 5.709 inches

### Mechanical data

Internal wiring	1.5 mm <sup>2</sup>
Use	Supply cable entry
Coding	A
Mounting type	Wall, screw mount Installation on mounting plate

### Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	black
Contact Plating	Tin
Fire load	17.754 MJ
Weight	323.8 g

### Environmental requirements

Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C
--	--

### Commercial data

PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4066966816273
Customs tariff number	85366990990

### Product Classification

UNSPSC	39121406
ETIM 9.0	EC002567
ETIM 10.0	EC002567
ECCN	NO US CLASSIFICATION

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

### Downloads

#### Environmental Product Compliance

##### Compliance Search

Environmental Product  
Compliance  
899-631/460-000



## 1 Compatible Products

### 1.1 System counterpart

#### 1.1.1 Cable assembly



**Item No.: 771-9994/206-101**

pre-assembled connecting cable; Eca;  
Plug/open-ended; 4-pole; Cod. A; H05VV-  
F 4G 1.5 mm<sup>2</sup>; 1 m; 1,50 mm<sup>2</sup>; black

**Item No.: 771-9994/006-101**

pre-assembled interconnecting cable;  
Eca; Socket/plug; 4-pole; Cod. A; H05VV-  
F 4G 1.5 mm<sup>2</sup>; 1 m; 1,50 mm<sup>2</sup>; black

#### 1.1.2 Male connector/plug



**Item No.: 770-214**

Plug; 4-pole; Cod. A; 4,00 mm<sup>2</sup>; black

**Item No.: 770-114**

Plug; with strain relief housing; 4-pole;  
Cod. A; 4,00 mm<sup>2</sup>; black

## 1.2 Optional Accessories

### 1.2.1 Installation

#### 1.2.1.1 Mounting accessories



**Item No.: 899-680**

Mounting plate; for distribution boxes; gray