



PHOTOMETRIC LIGHT REPORT

Philips LED strip | Fortimo LEDFlex 5m 2000lm/m 940PW C5 G1

Article number: 127-632

PHILIPS



Go to the
webshop
of Tronix
Lighting



TRONIX

127-632 Philips LED strip | Fortimo LEDFlex 5m 2000lm/m 940PW C5 G1

Introduction

Purpose of this Document

This document provides accurate and objective photometric data for Signify Netherlands BV item 127-632. All information is based on actual measurements taken from standard production units. No modifications were made to enhance performance results. In some cases, minor adjustments—such as temporary removal of covers, cables, or mounting features—were necessary for testing purposes. These did not influence product performance.

Test Methodology

Testing was conducted using randomly selected, unopened samples from regular inventory. All tests comply with the LM-79-19 standard, the recognized method for photometric and electrical measurements of LED and OLED luminaires. This standard, an update of IES LM-79-2008, outlines environmental test conditions, stabilization procedures, measurement methods, and approved instruments. It uses absolute photometry, meaning results directly reflect the performance of the tested product, without comparison to rated lamp standards.

Product 127-632 was tested using:

- A photogoniometer to measure luminous intensity distribution at various angles
- An integrating sphere to determine total luminous flux and colour characteristics

Compliance & Certification

Item 127-632 meets the requirements of the following EU directives. Signify Netherlands BV certifies that all relevant tests were executed in accordance with the applicable standards, and the CE mark is applied accordingly:

- General Product Safety – Directive 2023/988/EC
- Low Voltage Directive (LVD) – Directive 2014/35/EU
- Electromagnetic Compatibility (EMC) – Directive 2004/108/EC
- Ecodesign – Directive 2009/125/EC
- RoHS 3 – Directive 2011/65/EU + Amendment 2015/863/EU

Recycling & Sustainability

Signify Netherlands BV is affiliated with national recycling systems for electrical and electronic waste. The luminaire is over 90% recyclable when disposed of as electronic waste at end of life. In addition, Signify Netherlands BV participates in national packaging recycling schemes, ensuring full compliance with both the WEEE and packaging directives.

127-632 Philips LED strip | Fortimo LEDFlex 5m 2000lm/m 940PW C5 G1

Laboratory and equipment

Laboratory owner and location	Tronix Lighting BV. Uden. The Netherlands
Gonio spectrometer system and type	Viso Systems Type C. horizontal
Spectrometer manufacturer and model	(Gonio) Ocean Optics STS VIS (Sphere) Admesy HERA VIS 380–780nm
Flicker meter manufacturer and model	Viso Systems LabFlicker
Oscilloscope manufacturer and model	Tektronix MDO3024 oscilloscope (4 Channels. 200 MHz)
Power meter manufacturer and model	Vitretek PA900 Precision Multi-Channel Harmonic Power Analyzer
Power source manufacturer and model	(DC) Keithley Source Measure Unit SMU-2420 3A DC Source Meter (AC) Chroma 61601 AC Source
Datalogger Manufacturer and Model	Omega 8-Channel Thermocouple Thermometer/Data Logger

Measurement conditions gonio spectrometer

Number of C-planes and Resolution	2 planes – 180°
γ (gamma)-Resolution	2.5°
Test Distance	1.14 m
Room Temperature and Humidity	22°C +/- 10% – RH 50% +/- 20%
Input Power. Power and Displacement Factors	16.0 W – PF 1.0 – DPF 0.7
Frequency of Input Power	0 Hz
Warm-up Time and Variation	Not completed – +99.9%

Tested light source

Manufacturer and Order Code	Signify Netherlands BV – 127-632
Product Description	Philips LED strip Fortimo LEDFlex 5m 2000lm/m 940PW C5 G1 Signify: 929001490180

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	1868 lm – 0% / 100%
Efficiency	116 lm/W
Energy efficiency class	F
Peak Intensity and Beam Angle	625 cd – 116.9°
Correlated Colour Temperature	CCT = 4133 K
Colour Shift. CIE duv	Duv -0.0056
Colour Rendering Index	CRI 93.7
Colour Rendering TM30-18	R _f 88.5 – R _g 97.1
Television Lighting Consistency Index	TLCI = 94
Flicker	SVM n/a – PstLM n/a

127-632 Philips LED strip | Fortimo LEDFlex 5m 2000lm/m 940PW C5 G1

Electrical measurement details

Input Power


RMS Input voltage feed. V_{RMS} 24.0 V
 RMS Input current feed. I_{RMS} 0.669 A
 Total input power 16.0 W

Frequency of input power 0 Hz
 Power factor 1.0
 Displacement power factor 0.7

Total harmonic distortion of the current 0%
 Total harmonic distortion of the voltage 0%

Input Power Curve

Voltage - Current



Efficiency

Radiated power efficiency: 41.4%




Lumen efficiency: 116 lm/W



Harmonics

3rd Harmonic n/a
 5th Harmonic n/a
 7th Harmonic n/a
 9th Harmonic n/a
 11th Harmonic n/a

Current Harmonics %



Stabilization Details

Warm-up Conditions

Stable period 15 min
 Stable change max 2.0%
 Minimum warm-up time 15 min

Colour temperature change during warm-up

CCT start 12947 K
 CCT shift -8814 K
 CCT end 4133 K

Warm-up Results

Total warmup time Not completed
 Warmup variation +99.9%

Output intensity change during warm-up

Output start 262 lm
 Output change +1606 lm
 Output end 1868 lm


127-632 Philips LED strip | Fortimo LEDFlex 5m 2000lm/m 940PW C5 G1

Colour measurement details


Total lumen output 1868 lm
 Correlated Colour Temperature 4133 K
 Colour coordinates CIE 1931 (x;y) = (0.372;0.360)
 Colour deviation from BBL Duv = -0.0056

TM30-18 Colour Fidelity Index R_f 88.5
 TM30-18 Colour Gamut Index R_g 97.1
 Colour Rendering Index (Ra) CRI 93.7
 Colour Rendering Index. (red component) $R_9 = 83.3$


Colour Quality Scale CQS = 91.4
 Television Lighting Consistency Index TLCI = 94



Relative spectral power distribution



TM30 details




TM30 Colour vectors per hue bin




TM30 Colour distortion


Hue Bin	R_f	Shifts (%)	
		Chroma	Hue
C1	90	-3%	2%
C2	93	-1%	2%
C3	94	-1%	1%
C4	90	-4%	-2%
C5	89	-8%	-2%
C6	93	-4%	0%
C7	89	-6%	4%
C8	87	-3%	7%
C9	83	-1%	13%
C10	82	1%	11%
C11	84	6%	8%
C12	91	5%	-1%
C13	89	3%	-7%
C14	93	-1%	-2%
C15	85	-1%	-7%
C16	86	-2%	-5%



TM30-18 R_f -values per reference colour




TM30-18 R_f -values per hue bin




TM30 Chroma shift

Colour Quality details



Colour Rendering Index



Colour Quality Scale

127-632 Philips LED strip | Fortimo LEDFlex 5m 2000lm/m 940PW C5 G1

Flicker / temporal light artefacts details

Measurement conditions

Flicker meter type	Viso Systems LabFlicker
Flicker/TLA sample rate	n/a samples/s
Measurement time	5x 180 seconds (15 minutes) for PstLM. 1.2 sec for all other indices

Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency	n/a Hz
Percent flicker	n/a %
Flicker index	n/a

TLA indices (according IEC TR 61547-1, EN 61000-3-3 and EN 61000-4-15)

An LED luminaire is considered flicker-free if the SVM value is ≤ 0.4 and if the PstLM value is ≤ 1.0

PstLM value ($F < 80$ Hz)	n/a
SVM value ($80 < F < 2000$ Hz)	n/a

Flicker frame (one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789-2015 Lighting Flicker Risk Zones




Document revision date: 1-7-2025 Measurement serial: VFR-250219-3124-MS

127-632 Philips LED strip | Fortimo LEDFlex 5m 2000lm/m 940PW C5 G1

Beam angle

Luminous Intensity diagram

Unit: 0-100% of peak intensity



116,9°

Main Values

Output (total Lumen)	1868 lm
Lumen Up/Down	0% / 100%
Peak Intensity	625 cd
Beam Angle (50%)	116.9°
Beam Angle (90%)	116.9°
Beam Angle (10%)	116.9°

Cut-off Angle

Average 2.5%	176.1°
--------------	--------

Field Angle

Average 10%	162.2°
-------------	--------

Intensity Ratio

In 120° cone	78.1%
In 90° cone	52.5%

C planes


C000-C180
C090-C270

Linear distribution diagram - Intensity (candela) vs γ-angle



Document revision date: 1-7-2025 Measurement serial: VFR-250219-3124-MS

Beam Details



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6	ft
625	156	69	39	25	17	13	10	8	6	5	4	4	3	3	2	2	2	2	2	lux
58.1	14.5	6.5	3.6	2.3	1.6	1.2	0.9	0.7	0.6	0.5	0.4	0.3	0.3	0.3	0.2	0.2	0.2	0.2	0.1	fc

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
625	622	615	604	587	566	541	511	477	438	395	347	296	241	184	126	73	32	2	0	cd
100%	100%	98%	97%	94%	91%	87%	82%	76%	70%	63%	56%	47%	39%	29%	20%	12%	5%	0%	0%	of 0°val

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
625	622	615	604	587	566	541	511	477	438	395	347	296	241	184	126	73	32	2	0	cd
100%	100%	98%	97%	94%	91%	87%	82%	76%	70%	63%	56%	47%	39%	29%	20%	12%	5%	0%	0%	of 0°val

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
625	622	615	604	587	566	541	511	477	438	395	347	296	241	184	126	73	32	2	0	cd
100%	100%	98%	97%	94%	91%	87%	82%	76%	70%	63%	56%	47%	39%	29%	20%	12%	5%	0%	0%	of 0°val

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
625	622	615	604	587	566	541	511	477	438	395	347	296	241	184	126	73	32	2	0	cd
100%	100%	98%	97%	94%	91%	87%	82%	76%	70%	63%	56%	47%	39%	29%	20%	12%	5%	0%	0%	of 0°val

127-632 Philips LED strip | Fortimo LEDFlex 5m 2000lm/m 940PW C5 G1

Light Planning – UGR table

Uncorrected, comprehensive UGR table according to CIE 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	26.8	28.0	27.0	28.3	28.5	28.7	30.0	29.0	30.3	30.5
	3H	27.7	29.0	28.2	29.3	29.5	30.2	31.5	30.6	31.8	32.0
	4H	28.1	29.3	28.5	29.6	29.8	30.8	32.0	31.2	32.3	32.5
	6H	28.3	29.4	28.6	29.7	30.1	31.3	32.3	31.6	32.6	33.0
	8H	28.3	29.4	28.7	29.7	30.1	31.4	32.4	31.7	32.7	33.1
	12H	28.3	29.3	28.7	29.7	30.1	31.4	32.5	31.8	32.8	33.2
4H	2H	27.4	28.6	27.8	28.9	29.1	28.9	30.2	29.4	30.4	30.7
	3H	28.6	29.6	29.0	30.0	30.4	30.7	31.7	31.0	32.0	32.5
	4H	29.0	29.9	29.4	30.3	30.9	31.3	32.2	31.7	32.6	33.2
	6H	29.2	30.1	29.7	30.5	30.8	31.7	32.6	32.2	33.0	33.4
	8H	29.2	30.1	29.8	30.4	30.8	31.9	32.7	32.4	33.1	33.5
	12H	29.3	29.9	29.7	30.4	30.8	32.0	32.7	32.5	33.1	33.6
8H	4H	29.2	30.0	29.7	30.4	30.8	31.3	32.1	31.8	32.5	32.9
	6H	29.5	30.1	30.0	30.6	31.2	31.9	32.5	32.4	33.0	33.5
	8H	29.6	30.2	30.1	30.7	31.3	32.1	32.6	32.6	33.2	33.8
	12H	29.7	30.1	30.2	30.6	31.2	32.2	32.7	32.8	33.2	33.8
12H	4H	29.2	29.9	29.7	30.3	30.8	31.3	32.0	31.8	32.4	32.9
	6H	29.6	30.1	30.1	30.6	31.3	31.9	32.4	32.4	33.0	33.6
	8H	29.7	30.1	30.2	30.6	31.2	32.1	32.5	32.7	33.0	33.7
Variations with the observer position for the luminaire spacings. S:											
S = 1.0H		0.1 / -0.2					0.1 / -0.2				
S = 1.5H		0.3 / -0.6					0.5 / -0.6				
S = 2.0H		0.7 / -1.1					1.2 / -1.3				

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)																	
	Room Values are expressed as percentage of Lumen delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	109	104	99	95	106	101	97	94	97	94	91	93	91	88	90	87	85	83
2	98	90	83	77	96	88	82	76	85	79	75	81	77	73	78	75	71	69
3	90	79	71	64	87	77	70	63	74	68	62	72	66	61	69	64	60	58
4	82	70	61	54	80	68	60	54	66	59	53	63	57	52	61	56	51	49
5	75	62	53	46	73	61	52	46	59	51	45	57	50	45	55	49	44	42
6	69	56	47	40	67	55	46	40	53	45	40	51	45	39	50	44	39	37
7	64	51	42	35	63	50	41	35	48	41	35	47	40	35	45	39	35	33
8	60	46	37	32	58	45	37	31	44	37	31	43	36	31	42	35	31	29
9	56	42	34	28	54	42	34	28	40	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	36	30	25	23