



PHOTOMETRIC LIGHT REPORT

Philips LED strip | Fortimo LEDFlex 5m 1000lm/m 927 C5 G1

Article number: 127-600

PHILIPS



Go to the
webshop
of Tronix
Lighting



TRONIX

127-600 Philips LED strip | Fortimo LEDFlex 5m 1000lm/m 927 C5 G1

Introduction

Purpose of this Document

This document provides accurate and objective photometric data for Signify Netherlands BV item 127-600. All information is based on actual measurements taken from standard production units. No modifications were made to enhance performance results. In some cases, minor adjustments—such as temporary removal of covers, cables, or mounting features—were necessary for testing purposes. These did not influence product performance.

Test Methodology

Testing was conducted using randomly selected, unopened samples from regular inventory. All tests comply with the LM-79-19 standard, the recognized method for photometric and electrical measurements of LED and OLED luminaires. This standard, an update of IES LM-79-2008, outlines environmental test conditions, stabilization procedures, measurement methods, and approved instruments. It uses absolute photometry, meaning results directly reflect the performance of the tested product, without comparison to rated lamp standards.

Product 127-600 was tested using:

- A photogoniometer to measure luminous intensity distribution at various angles
- An integrating sphere to determine total luminous flux and colour characteristics

Compliance & Certification

Item 127-600 meets the requirements of the following EU directives. Signify Netherlands BV certifies that all relevant tests were executed in accordance with the applicable standards, and the CE mark is applied accordingly:

- General Product Safety – Directive 2023/988/EC
- Low Voltage Directive (LVD) – Directive 2014/35/EU
- Electromagnetic Compatibility (EMC) – Directive 2004/108/EC
- Ecodesign – Directive 2009/125/EC
- RoHS 3 – Directive 2011/65/EU + Amendment 2015/863/EU

Recycling & Sustainability

Signify Netherlands BV is affiliated with national recycling systems for electrical and electronic waste. The luminaire is over 90% recyclable when disposed of as electronic waste at end of life. In addition, Signify Netherlands BV participates in national packaging recycling schemes, ensuring full compliance with both the WEEE and packaging directives.

127-600 Philips LED strip | Fortimo LEDFlex 5m 1000lm/m 927 C5 G1

Laboratory and equipment

Laboratory owner and location	Tronix Lighting BV. Uden. The Netherlands
Gonio spectrometer system and type	Viso Systems Type C. horizontal
Spectrometer manufacturer and model	(Gonio) Ocean Optics STS VIS (Sphere) Admesy HERA VIS 380–780nm
Flicker meter manufacturer and model	Viso Systems LabFlicker
Oscilloscope manufacturer and model	Tektronix MDO3024 oscilloscope (4 Channels. 200 MHz)
Power meter manufacturer and model	Vitretek PA900 Precision Multi-Channel Harmonic Power Analyzer
Power source manufacturer and model	(DC) Keithley Source Measure Unit SMU-2420 3A DC Source Meter (AC) Chroma 61601 AC Source
Datalogger Manufacturer and Model	Omega 8-Channel Thermocouple Thermometer/Data Logger

Measurement conditions gonio spectrometer

Number of C-planes and Resolution	2 planes – 180°
γ (gamma)-Resolution	2.5°
Test Distance	1.14 m
Room Temperature and Humidity	22°C +/- 10% – RH 50% +/- 20%
Input Power. Power and Displacement Factors	8.7 W – PF 1.0 – DPF 0.71
Frequency of Input Power	0 Hz
Warm-up Time and Variation	n/a – n/a%

Tested light source

Manufacturer and Order Code	Signify Netherlands BV – 127-600
Product Description	Philips LED strip Fortimo LEDFlex 5m 1000lm/m 927 C5 G1 Signify: 929001489480

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	924 lm – 0% / 100%
Efficiency	106 lm/W
Energy efficiency class	F
Peak Intensity and Beam Angle	315 cd – 115.5°
Correlated Colour Temperature	CCT = 2716 K
Colour Shift. CIE duv	Duv -0.0010
Colour Rendering Index	CRI 94.7
Colour Rendering TM30-18	R _f 91.1 – R _g 97.3
Television Lighting Consistency Index	TLCI = 94
Flicker	SVM n/a – PstLM n/a

127-600 Philips LED strip | Fortimo LEDFlex 5m 1000lm/m 927 C5 G1

Electrical measurement details

Input Power

RMS Input voltage feed. V_{RMS} 24.0 V
 RMS Input current feed. I_{RMS} 0.364 A
 Total input power 8.7 W

Frequency of input power 0 Hz
 Power factor 1.0
 Displacement power factor 0.71

Total harmonic distortion of the current 0%
 Total harmonic distortion of the voltage 0%

Input Power Curve

Voltage - Current



Efficiency

Radiated power efficiency: 38.4%



Lumen efficiency: 106 lm/W



Harmonics

3rd Harmonic n/a
 5th Harmonic n/a
 7th Harmonic n/a
 9th Harmonic n/a
 11th Harmonic n/a

Current Harmonics %



Stabilization Details

Warm-up Conditions

Stable period
 Stable change max
 Minimum warm-up time

Colour temperature change during warm-up

n/a CCT start n/a K
 n/a% CCT shift n/a K
 n/a CCT end 2716 K

Warm-up Results

Total warmup time
 Warmup variation

Output intensity change during warm-up

n/a Output start n/a lm
 n/a% Output change n/a lm
 Output end 924 lm


127-600 Philips LED strip | Fortimo LEDFlex 5m 1000lm/m 927 C5 G1

Colour measurement details


Total lumen output 924 lm
 Correlated Colour Temperature 2716 K
 Colour coordinates CIE 1931 (x;y) = (0.457;0.407)
 Colour deviation from BBL Duv = -0.0010

TM30-18 Colour Fidelity Index R_f 91.1
 TM30-18 Colour Gamut Index R_g 97.3
 Colour Rendering Index (Ra) CRI 94.7
 Colour Rendering Index. (red component) $R_9 = 69.5$


Colour Quality Scale CQS = 92.3
 Television Lighting Consistency Index TLCI = 94



Relative spectral power distribution



TM30 details




TM30 Colour vectors per hue bin




TM30 Colour distortion


Hue Bin	R_f	Shifts (%)	
		Chroma	Hue
C1	91	-4%	2%
C2	94	-2%	1%
C3	96	-1%	1%
C4	91	-5%	-3%
C5	94	-5%	0%
C6	95	-2%	1%
C7	91	-5%	3%
C8	94	-1%	4%
C9	89	0%	7%
C10	89	2%	8%
C11	90	5%	6%
C12	90	5%	-3%
C13	89	1%	-8%
C14	88	1%	-10%
C15	90	-5%	-1%
C16	86	-3%	-10%



TM30-18 R_f -values per reference colour




TM30-18 R_f -values per hue bin




TM30 Chroma shift

Colour Quality details



Colour Rendering Index



Colour Quality Scale

127-600 Philips LED strip | Fortimo LEDFlex 5m 1000lm/m 927 C5 G1

Flicker / temporal light artefacts details

Measurement conditions

Flicker meter type	Viso Systems LabFlicker
Flicker/TLA sample rate	n/a samples/s
Measurement time	5x 180 seconds (15 minutes) for PstLM. 1.2 sec for all other indices

Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency	n/a Hz
Percent flicker	n/a %
Flicker index	n/a

TLA indices (according IEC TR 61547-1, EN 61000-3-3 and EN 61000-4-15)

An LED luminaire is considered flicker-free if the SVM value is ≤ 0.4 and if the PstLM value is ≤ 1.0

PstLM value ($F < 80$ Hz)	n/a
SVM value ($80 < F < 2000$ Hz)	n/a

Flicker frame (one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789-2015 Lighting Flicker Risk Zones




Document revision date: 1-7-2025 Measurement serial: VFR-250219-3098-MS

127-600 Philips LED strip | Fortimo LEDFlex 5m 1000lm/m 927 C5 G1

Beam angle

Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	924 lm
Lumen Up/Down	0% / 100%
Peak Intensity	315 cd
Beam Angle (50%)	115.5°
Beam Angle (90%)	115.5°
Beam Angle (10%)	115.5°

Cut-off Angle

Average 2.5%	173.1°
--------------	--------

Field Angle

Average 10%	160.8°
-------------	--------


Intensity Ratio

In 120° cone	78.7%
In 90° cone	53.1%

C planes

C000-C180
C090-C270


Linear distribution diagram - Intensity (candela) vs γ-angle



Document revision date: 1-7-2025 Measurement serial: VFR-250219-3098-MS

127-600 Philips LED strip | Fortimo LEDFlex 5m 1000lm/m 927 C5 G1

Beam Details



*Measured at center of beam

Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6	ft
315	79	35	20	13	9	6	5	4	3	3	2	2	2	1	1	1	1	1	1	lux
29.3	7.3	3.3	1.8	1.2	0.8	0.6	0.5	0.4	0.3	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	fc

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
315	314	310	304	295	284	271	255	237	217	196	172	146	118	90	61	33	12	1	0	cd
100%	100%	98%	96%	94%	90%	86%	81%	75%	69%	62%	54%	46%	38%	28%	19%	11%	4%	0%	0%	of 0°val

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
315	314	310	304	295	284	271	255	237	217	196	172	146	118	90	61	33	12	1	0	cd
100%	100%	98%	96%	94%	90%	86%	81%	75%	69%	62%	54%	46%	38%	28%	19%	11%	4%	0%	0%	of 0°val

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
315	314	310	304	295	284	271	255	237	217	196	172	146	118	90	61	33	12	1	0	cd
100%	100%	98%	96%	94%	90%	86%	81%	75%	69%	62%	54%	46%	38%	28%	19%	11%	4%	0%	0%	of 0°val

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
315	314	310	304	295	284	271	255	237	217	196	172	146	118	90	61	33	12	1	0	cd
100%	100%	98%	96%	94%	90%	86%	81%	75%	69%	62%	54%	46%	38%	28%	19%	11%	4%	0%	0%	of 0°val

127-600 Philips LED strip | Fortimo LEDFlex 5m 1000lm/m 927 C5 G1

Light Planning – UGR table

Uncorrected, comprehensive UGR table according to CIE 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	24.3	25.5	24.5	25.9	26.1	26.3	27.5	26.5	27.8	28.0
	3H	25.3	26.5	25.7	26.8	27.0	27.7	29.0	28.1	29.3	29.5
	4H	25.6	26.8	26.0	27.1	27.4	28.3	29.5	28.7	29.8	30.0
	6H	25.8	26.9	26.1	27.2	27.5	28.7	29.8	29.0	30.1	30.4
	8H	25.8	26.9	26.2	27.2	27.6	28.8	29.8	29.2	30.2	30.6
	12H	25.8	26.8	26.2	27.1	27.6	28.8	29.8	29.2	30.2	30.6
4H	2H	24.9	26.1	25.3	26.4	26.7	26.5	27.7	26.9	28.0	28.2
	3H	26.1	27.1	26.5	27.5	27.9	28.2	29.2	28.6	29.5	30.0
	4H	26.5	27.4	26.9	27.8	28.4	28.8	29.7	29.2	30.1	30.6
	6H	26.7	27.6	27.2	27.9	28.3	29.2	30.1	29.7	30.4	30.8
	8H	26.7	27.5	27.2	27.9	28.3	29.3	30.1	29.8	30.5	30.9
	12H	26.7	27.4	27.2	27.8	28.3	29.4	30.0	29.9	30.5	30.9
8H	4H	26.7	27.5	27.2	27.9	28.2	28.8	29.6	29.3	30.0	30.4
	6H	27.0	27.6	27.5	28.1	28.6	29.3	29.9	29.8	30.4	30.9
	8H	27.1	27.6	27.6	28.1	28.8	29.5	30.0	30.0	30.5	31.2
	12H	27.1	27.5	27.7	28.0	28.6	29.6	30.0	30.2	30.5	31.1
12H	4H	26.7	27.3	27.2	27.8	28.2	28.8	29.4	29.3	29.9	30.3
	6H	27.0	27.6	27.5	28.1	28.7	29.3	29.9	29.8	30.4	31.0
	8H	27.1	27.5	27.7	28.0	28.7	29.5	29.9	30.1	30.4	31.0
Variations with the observer position for the luminaire spacings. S:											
S = 1.0H		0.2 / -0.2					0.2 / -0.2				
S = 1.5H		0.3 / -0.6					0.6 / -0.7				
S = 2.0H		0.8 / -1.2					1.2 / -1.3				

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)																	
	Room Values are expressed as percentage of Lumen delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	109	104	100	96	106	102	98	94	97	94	91	93	91	88	90	88	86	84
2	99	90	84	78	96	89	82	77	85	80	75	82	77	73	79	75	72	69
3	90	79	71	64	87	78	70	64	75	68	63	72	66	62	69	65	61	58
4	82	70	61	54	80	69	60	54	66	59	53	64	58	53	62	56	52	50
5	76	63	53	47	73	61	53	46	59	52	46	57	51	45	55	50	45	43
6	70	56	47	41	68	55	47	41	53	46	40	52	45	40	50	44	39	37
7	65	51	42	36	63	50	42	36	49	41	35	47	40	35	46	40	35	33
8	60	46	38	32	58	46	38	32	44	37	32	43	36	31	42	36	31	29
9	56	43	34	29	55	42	34	29	41	34	28	40	33	28	39	33	28	26
10	53	39	31	26	51	39	31	26	38	31	26	37	30	26	36	30	26	24