


Walraven RapidRail® Light-Duty Channel

(G0406)

channels for light-duty applications



Features & benefits

- C-profile
- for quick and adjustable fixing of one or multiple pipes
- with continuous perforation
- distance between rail end and first hole is always equal
- with sawing marks each 50 mm
- flexible hole pattern with anchor holes and also small holes to use wood screws
- unique hole pattern at rail 30x20 allows to click in Walraven RapidRail® Hammerfix from both sides
- special hole pattern and material thickness for 32x20 rail
- material: steel 1.0242
- pre-galvanized
- for more information about the max. allowed load (Faz) please refer to the loading tables or our online datasheet 'Technical Details Walraven RapidRail®'



Product Number	Type	Total Height	Total Width	Total Length	Material Thickness	Profile Opening
Reference Letter		H	W	L	MT	S
Unit description		mm	mm	mm	mm	mm
650527182	27x18	18	27	2,000	1.00	15
650527183	27x18	18	27	3,000	1.00	15
650527184	27x18	18	27	4,000	1.00	15
650527186	27x18	18	27	6,000	1.00	15
650530150	30x15	15	30	500	1.50	15
650530152	30x15	15	30	2,000	1.50	15
650530153	30x15	15	30	3,000	1.50	15
650530156	30x15	15	30	6,000	1.50	15
650530202	30x20	20	30	2,000	1.25	15
650530203	30x20	20	30	3,000	1.25	15
650530206	30x20	20	30	6,000	1.25	15
650530302	30x30	30	30	2,000	1.50	15
650530303	30x30	30	30	3,000	1.50	15
650530306	30x30	30	30	6,000	1.50	15
6505232	32x20	20	32	2,000	2.50	16