



ENERG
енергия · ενεργεια



10053302

alpha innotec

LW 140 L



55 °C

35 °C



A⁺⁺

A⁺⁺



58 dB



56 dB

■ 13
■ 14
■ 16
kW

■ 13
■ 14
■ 16
kW





ENERGY

10053302

alpha innotec

LW 140 L



55 °C

35 °C

A⁺⁺⁺

A⁺⁺

A⁺

A

B

C

D

A⁺⁺

A⁺⁺



58 dB



56 dB

■ 13
■ **14**
■ 16
kW

■ 13
■ **14**
■ 16
kW





ENERG
енергия · ενεργεια

Y

IJA

IE

IA

10053302

alpha innotec

LW 140 L + Luxtronik 2.0



A⁺⁺

A⁺⁺⁺

A⁺⁺

A⁺⁺

A⁺

A

B

C


D

E

F

G

+



+



+



+



package (heat pumps and combination heater with heat pump) - LW 140 L + Luxtronik 2.0												
Seasonal space heating energy efficiency of heat pump (η_s)					1	125	%					
Rated heat output of the heat pump (P_{rated} kW)					14							
Temperature control		Class	III	(Table 1)	+	2	1,5	%				
Supplementary boiler												
package with hot water storage tank		no	P_{sup} kW (rated heat output of supplementary heater)									
		η_s % (σ_{π})										
		$(\eta_s \text{ % (sup)} - 1) \times (\alpha_{WP}) =$					3		%			
(aWE: see Table 3)			(α_{WE})									
solar contribution			$(A_{Koll} \text{ m}^2)$		$(\eta_{Koll} \text{ %})$							
			$(V_{Sp} \text{ m}^3)$		(standstill heat loss of the hot water storage tank in W)							
					$(\eta_{Sp}: \text{Table 2})$							
					$((294/P_{rated} \times 11) \times (A_{Koll} \text{ m}^2) + (115/P_{rated} \times 11) \times (V_{Sp} \text{ m}^3)) \times 0,45 \times ((\eta_{Koll} \text{ %}) / 100) \times (\eta_{Sp}) =$					4		%
Seasonal space heating energy efficiency of package					5	127	%					
					rounded to the nearest integer							
Seasonal space heating energy efficiency class of package												
X G F E D C B A A⁺ A⁺⁺ A⁺⁺⁺ < 30 % ≥ 30 % ≥ 34 % ≥ 36 % ≥ 75 % ≥ 82 % ≥ 90 % ≥ 98 % ≥ 125 % ≥ 150 %												
Seasonal space heating energy efficiency under colder or warmer climate conditions												
Seasonal space heating energy efficiency of the heat pump (η_s) under colder climate conditions						115	%					
Seasonal space heating energy efficiency of the heat pump (η_s) under warmer climate conditions						152	%					
colder 5	127	-V	10	=	117	warmer 5	127	+VI	27	=	154	

heatpump datasheet:			
manufacturer:		alpha innotec	
model:		LW 140 L	
Information concerning energy efficiency class and rated heat output:			
	average / low	average / medium	
energy efficiency class space heater:	A++	A++	-
rated heat output:	14	14	kW
energy efficiency space heater:	157	125	%
annual final energy consumption space heater	7447	8842	kWh
sound power level indoors		58	dB
special precautions concerning assembly, installation or maintenance			
All instructional work in this manual may only be carried out by qualified specialist personnel in compliance with local regulations.			
additional information	low	medium	
rated heat output colder climate	13	13	kW
rated heat output warmer climate	16	16	kW
energy efficiency space heater colder climate	140	115	%
energy efficiency space heater warmer climate	190	152	%
annual energy consumption space heater colder climate	9044	10533	kWh
annual energy consumption space heater warmer climate	4553	5391	kWh
sound power level outdoors		56	dB

technical data of the temperature controller		
manufacturer:	alpha innotec	
model:	Luxtronik 2.0	
controller class	III	-
contribution of the controller to the energy efficiency space heater	1,5	%

Model				LW 140 L			
Air-to-water heat pump: (yes/no)				yes			
Brine-to-water heat pump: (yes/no)				no			
Water-to-water heat pump: (yes/no)				no			
Low-temperature heat pump: (yes/no)				no			
Equipped with supplementary heater: (yes/no)				yes			
combination heater with: (yes/no)				no			
application: (low/medium)				low			
climate: (colder/average/warmer)				average			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output	Prated	14	kW	Seasonal space heating energy efficiency	η_S	157,1	%
Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	11,0	kW	Tj = -7°C	COPd	3,13	-
Tj = +2°C	Pdh	13,9	kW	Tj = +2°C	COPd	3,94	-
Tj = +7°C	Pdh	14,5	kW	Tj = +7°C	COPd	4,94	-
Tj = +12°C	Pdh	16,4	kW	Tj = +12°C	COPd	5,43	-
Tj = bivalent temperature	Pdh	11,7	kW	Tj = bivalent temperature	COPd	3,34	-
Tj = operation limit temperature	Pdh	10,2	kW	Tj = operation limit temperature	COPd	2,87	-
For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)	COPd	-	-
Bivalent temperature	T _{biv}	-5	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	P _{psych}	-	kW	Cycling interval efficiency	COP _{cyc}	-	-
Degradation co-efficient (**)	Cdh	1,0	-	Heating water operating limit temperature	WTOL	50	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0,010	kW	Rated heat output	P _{sup}	4,3	kW
Thermostat-off mode	P _{TO}	0,010	kW	Type of energy input	electrical		
Standby mode	P _{SB}	0,010	kW				
Crankcase heater mode	P _{CK}	-	kW				
Other items							
Capacity control	fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	5.600	m³/h
sound power level, indoors/outdoors	L _{WA}	58 / 56	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h
Emissions of nitrogen oxides	NO _x	-	mg/kWh				
For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh
Contact details	ait deutschland GmbH Industriestr. 3 95359 Kasendorf Germany						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).							
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							