

Data Sheet | Item Number: 726-906

Insulation stop; 0.25 mm² "s"; 0.14 - 0.25 mm² "f-st"; 4 x 3 pieces/strip; light gray

<https://www.wago.com/726-906>



Color: ■ light gray

Notes

Safety Information

Suitable for patchboard side (side 1) of 1.5 mm² matrix patchboards (front side differs from back side)

Connection Data

Connection 1

Solid conductor	0.25 mm ² / 22 AWG
Fine-stranded conductor	0.14 mm ² / 14 AWG
Strip length	8 ... 10 mm / 0.31 ... 0.39 inches

Material data

Note (material data)	Information on material specifications can be found here
Color	light gray
Fire load	0.02 MJ
Weight	0.7 g

Commercial data

Product Group	12 (Matrix Patch Board)
PU (SPU)	200 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918094238
Customs tariff number	39269097900

Product Classification

UNSPSC	39121409
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 10.0	EC002848
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 726-906	↓
--	---

Documentation

Bid Text

726-906	19.02.2019	xml 2.77 KB	↓
726-906	21.02.2019	docx 14.01 KB	↓

CAD/CAE-Data

CAE data

WSCAD Universe 726-906	↓
---------------------------	---

Installation Notes

Conductor termination



Inserting an insulation stop into conductor entry holes of matrix patchboards.



Insulation stop is in place.

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com