



## BAP-SV1610S: Stop valve DN10



### Commercial information

Henco stopbolkraan in messing. Met persaansluiting

#### Basic unit dimensions

Height	23 mm
Length	75 mm
Width	23 mm
Net weight	0.110 kg

#### Certificates

#### Applications

Potable water, Heating, Sanitary, Compressed air

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

Surface protection ball	None	Diameter bolt hole	16
Material secondary spindle seal	Ethylene-propylene diene monomer rubber (EPDM)	Outer pipe diameter connection 1	16 Millimetre
Nominal diameter connection 1	DN 8	Outer pipe diameter connection 2	10 Millimetre
Connection 1	Press sleeve	Medium temperature (continuous)	-10 70 Degrees celsius
With coupling connection 1	✓	Wrench width	0 Millimetre
Contour code connection 1	TH/BE	Wrench width union nut	0 Millimetre
Nominal diameter connection 2	DN 10		
Connection 2	External thread conical BSPT-R (ISO 7-1 / EN 10226-1)		
With coupling connection 2	✓		
Sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With drain valve	✗		
With drain possibility (connection)	✓		
With filter	✗		
With thermometer	✗		
Model	Straight		
With insulation shell	✗		
FM quality mark	✗		
UL quality mark	✗		
ULC quality mark	✗		
LPCB quality mark	✗		
Fire-safe	✗		
Medically clean	✗		
Grease-free	✗		
Full bore	✗		
KIWA certified	✗		