


## PRODUCT DATASHEET

**Type:** eFLOOR-PRO-60-1500  
**Art. Nr.:** 46116



### Short description

Heating mat extra thin 3,8mm, PFAS free, 7,5m², 50x1500cm, 450W 230V



### Product Description

The self-adhesive eFLOOR PRO mesh heating mat has been specially developed for use under tile and stone floors and is suitable for comfortable floor heating, complete room heating, or cold insulation on walls. Thanks to its low overall height of only 3.8 mm, the mat can also be used in renovations without any problems, as it requires only a minimal installation height. Factory assembly enables quick and easy installation. The heating mat has a dipolar design with only one connection cable, which further simplifies installation and saves time. The PFAS-free heating conductor is low-magnetic and its robust structure ensures high stability in the tile adhesive bed. The self-adhesive carrier mesh with a 12×12 mm grid ensures secure fixation to the substrate. eFLOOR PRO is available in five different power levels from 60 to 200 W/m², allowing it to be flexibly adapted to different requirements and room conditions. Customized designs in individual sizes, power ratings, voltages, or shapes are also available on request. The nominal temperature of the heating conductor is up to 90 °C. The system complies with protection class IPX7 and is designed in accordance with VDE 0700. The eFLOOR PRO heating mat is CE-compliant and VDE-tested. The heating conductor is designed using dipole technology, is PFAS-free and has a low magnetic field. The grid spacing is 12×12 mm and the heating conductor thickness is 3.2 mm. The connection cable is 4 m long and consists of 2×1.0 mm² with integrated protective braiding. The operating voltage is 230 V. As a protective measure, a residual current circuit breaker (RCD) with a 30 mA tripping current is required. This product is a stationary, electric floor heating unit for individual rooms; in order to meet the mandatory ecodesign requirements of Commission Regulation (EU) 2024/1103, it must be supplemented by a controller that fulfills at least the following control functions: electronic room temperature controller with weekday control (TW) and at least one f function (e.g., f2 or f4); the following combinations are possible: TW (f2), TW (f3), TW (f4), TW (f8)

### ETIM characteristics

<b>Model</b>	Heating cable	<b>Connection voltage</b>	230 23 Volt 0
<b>With support mat</b>	✓	<b>Connected load</b>	540 54 Watt 0
<b>Fixation thermal conductor</b>	Glued	<b>Power</b>	60 Watt per square metre
<b>Self-adhesive</b>	✓	<b>Heating conductor load</b>	5.4 Watt per metre
<b>Suitable for damp space</b>	✓	<b>Resistance</b>	98 Ohm
<b>Suitable as outdoor surface heating</b>	✗	<b>Number of cold conductors</b>	1
<b>Suitable as roof surface heating</b>	✗	<b>Length of cold conductors</b>	4000 Millimetre
<b>With controller</b>	✗	<b>Surface</b>	9 Square metre
<b>With room temperature controller</b>	✗	<b>Length</b>	18000 Millimetre
<b>With floor temperature sensor</b>	✗	<b>Width</b>	500 Millimetre
		<b>Thickness</b>	3.2 Millimetre

Created on: 27/06/2025