

Data Sheet | Item Number: 282-384

Lock-out; for disconnect link; yellow

<https://www.wago.com/282-384>



Color: ■ yellow

Material data

Note (material data)	Information on material specifications can be found here
Color	yellow
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.013 MJ
Weight	0.4 g

Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data

Product Group	1 (Rail Mounted Terminal Blocks)
PU (SPU)	100 (20) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332283212
Customs tariff number	39269097900

Product Classification	
UNSPSC	39121703
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 10.0	EC002848
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 282-384	↓

Documentation


Bid Text			
282-384	19.02.2019	xml 2.50 KB	↓
282-384	03.03.2017	doc 23.00 KB	↓

CAD/CAE-Data

CAD data	
2D/3D Models 282-384	↓

CAE data	
WSCAD Universe 282-384	↓
ZUKEN Portal 282-384	↓

Installation Notes



Lock-out snaps into one of two notched positions, preventing accidental operation of the disconnect link.

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com