



Product data sheet

Item No. 96.032.2053.1

Male connector RST20I3F S2 M00V SW

Device connectors, modular M20, RST20i3, 3 pole, straight, male, spring clamp connection, 250V/20A, color of coding: black, color of $\,$ housing: black



| Item No. | 96.032.2053.1 |
|------------|---------------|
| EAN | 4015573743779 |
| Order Unit | 100 Piece(s) |

Certificates / Approvals







Technical data

General

| Rated current | 20 A |
|--|-------|
| Rated voltage | 250 V |
| Pollution degree | 3 |
| Mechanical coding | Yes |
| Rated impulse voltage | 4 kV |
| Interlockable | Yes |
| Color of coding/ contact carrier | Black |
| Marking of poles | |
| Color of separate adapter (if present) | Black |

Connection Data

| Connection cross section solid | 2.5 mm² |
|-----------------------------------|---------|
| Connection cross section stranded | 1.5 mm² |
| Terminations per pole | 2 |

Model

| Model | male |
|-----------------|------|
| Number of poles | 3 |





| Connection type | Tension clamp connection |
|------------------------------|--|
| Connecting thread metric | M20 |
| Angle of plug | Straight |
| Degree of protection (IP) | IP66/IP68 |
| Remark to type of connection | Finely stranded con. req. Wieland cable end sleeve |
| Built-in component | Snap-in/screw-in |

Material

| Housing material | Polyamide |
|---|---------------|
| Halogen free | Yes |
| Contact material | CuZn |
| Insulation components continous temperature | 100 °C |
| Surface finish | Silver-plated |

Dimensions

| | Length | 65.3 mm |
|---|--------|---------|
| | Width | 35 mm |
| Ì | Height | 35 mm |

Technical drawing

