

Concord

OPTIX LINEAR SURFACE 1200 TW ALU DALI EM

2023824



Features

• OPTIX LINEAR SURFACE 1200 TW ALU DALI EM is a high efficacy low glare linear luminaire for office and education applications. Suitable for continuous light line installations with accessories separately available. Surface and suspended mounting. Size: 1160x90x80mm. Aluminised plastic extra low glare optics in a single line configuration. White RAL9016 fixture body. 3hr maintained emergency version. DALI DT8 colour control and dimming. Tunable white colour 3000-6000K, CRI>80, chromaticity tolerance of 3-step MacAdam ellipse. Luminous flux 2200lm. Power consumption 24W. Luminaire efficacy 92lm/W. Lifespan: 48,500 hours L90B10. UGR<19, Luminance at 65°<200 Cd/m², IK07, IP20. Ultra Low Flicker: <5% Photobiological safety risk group 1. Electrical protection Class I. Glow wire test 850°C.

Product Overview

Product name	OPTIX LINEAR SURFACE 1200 TW ALU DALI EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
Fixture rating	Enclosed
General application	Education, Office
ETIM Class	EC002892
Fixture luminous flux (lm)	2200
Luminaire efficacy (lm/W)	92
Light colour	Tunable White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 16


Concord
by SYLVANIA

Concord

OPTIX LINEAR SURFACE 1200 TW ALU DALI EM 2023824


Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	85
Total power consumption (W)	24
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9016
IP rating	IP20
IK rating	IK07
Product EAN number	5025768238248
Warranty	5 years
Dimming method	DALI

Photometry




Concord

OPTIX LINEAR SURFACE 1200 TW ALU DALI EM 2023824



Technical drawings



Data table

GENERAL DATA

Product name	OPTIX LINEAR SURFACE 1200 TW ALU DALI EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
Fixture rating	Enclosed
General application	Education, Office
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892

Concord

OPTIX LINEAR SURFACE 1200 TW ALU DALI EM 2023824

Warranty	5 years
----------	---------

OPTICAL DATA

Fixture luminous flux (lm)	2200
Luminaire efficacy (lm/W)	92
Light colour	Tuneable White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 16
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	85
Emergency duration (h)	3

ELECTRICAL DATA

Total power consumption (W)	24
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.97
THD (at 230 V, 50 Hz, full load, at 100% dimming level) \leq xx.x %	10
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
Drive current (mA)	400
Inrush Current (A)	29
Inrush Duration (μ s)	180
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 13A C Breaker	28

Concord

OPTIX LINEAR SURFACE 1200 TW ALU DALI EM 2023824

Max. products per 16A C Breaker	36
Max. products per 20A C Breaker	45
Max. products per 10A B Breaker	13
Max. products per 13A B Breaker	17
Max. products per 16A B Breaker	22
Max. products per 20A B Breaker	27
Connectable conductor cross section - Min (mm ²)	2.5
Connectable conductor cross section - Max (mm ²)	2.5

LIFETIME DATA

Lifespan L70 B50	120000
Lifespan L80 B20	107500
Lifespan L90 B10	48500

PHYSICAL DATA

Housing colour	RAL9016
IP rating	IP20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1160
Nominal Product Width (mm)	90
Nominal Product Height (mm)	80
Weight (kg)	4.0

PACKAGING

Product EAN number	5025768238248
Packaging single length / height (cm)	119.0
Packaging single width (cm)	10.0
Packaging single depth (cm)	11.0
DUN14 (inner)	05025768238248
Units per outer package	1

Concord

OPTIX LINEAR SURFACE 1200 TW ALU DALI EM

2023824

Packaging outer length / height (cm) 119.0

Packaging outer width (cm) 10.0

Packaging outer depth (cm) 11.0

SAFETY DATA

Special purpose lamp No

Dry applications use only No

Suitable for household illumination No

Concord
by SYLVANIA