

## 50-260320: Standard Ø26x3 50m



### Commercial information

Henco multilayer pipe with all the **advantages** of plastic and metal

- Butt welded aluminium pipe
- 100% oxygen-tight and water vapour diffusion tight
- Low coefficient of linear expansion, similar to metal pipe
- Entirely corrosion-resistant, also resistant against chemicals and electrochemicals
- Sound-insulation similar to entirely plastic pipe
- Electron beam crosslinked inner and outer pipe
- High resistance to pressure and temperature
- Smooth surface, less loss of pressure
- Light as synthetic piping
- Flexible, easy to bend even at low temperatures, retains shape after bending

#### Certificates

ATG, QB (CSTBat), DVGW Wasser, ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, WRAS, KOMO, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, Bureau Veritas, RISE, AFNOR, PZH, STF, ACS, DNV-GL, Aenor, Sans 21003, Kontrol Biro, EMI

#### Applications

Potable water, Heating, Cooling, Compressed air, Demi Water, Underfloor Heating, Sanitary






#### Solutions

Building installations, Industry, Underfloor heating, Utility, Shipbuilding

## Technical characteristics

Material inner layer	Plastic	Number of layers	5
Quality class inner layer	PEHD-Xc	Outer pipe diameter	26 Millimetre
Material intermediate layer	Aluminium	Wall thickness	3 Millimetre
Material outer layer	Plastic	Medium temperature (continuous)	- Degrees celsius 10 7 0
Quality class outer layer	PEHD-Xc	Max. medium temperature (momentarily)	95 Degrees celsius
Glass-fibre reinforced	✘	Max. operating pressure at 20 °C	16 Bar
Diffusion-proof	✓	Max. operating pressure at max. medium temperature	16 Bar
Nominal diameter	DN 20	Wall roughness	0.00 Millimetre 7
System specific	✓	Expansion coefficient	0.02 Millimetre per metre Kelvin 5
Flexible	✓	Min. bending radius	78 Millimetre
Suitable for surface mounting	✓	Min. bending radius without tools	78 Millimetre
Pipe colour	White	Outer diameter mantle pipe	0 Millimetre
With mantle pipe	✘	Thickness of thermal insulation	0 Millimetre
With heating cable	✘	Lambda value	0.43 Watt per meter Kelvin
With thermal insulation	✘	Outer diameter thermal insulation	0 Millimetre
SVGW certified	✘	Outer width rectangular insulation	0 Millimetre
Capped	✘	Outer height rectangular insulation	0 Millimetre
UV resistant	✘	Water content	0.31 Litre per metre 4
Halogen free	✓		
DIN-CERTCO certificate	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✓		
Compliant with NF 545	✓		
KOMO certified	✓		
Type approval according to BBR/EKS	✘		

## Related products

Product code	GTIN	Description	Image
BI-2620	05414764032958	Henco Internal Bending spring 26x3 l=100	
KS-K	05414764032958	Henco Clickhandle for KS (Kalispeed)	
DRILLY26	05414764032958	Henco Drilly temporary air vent plug reusable Ø26	
BM-26	05414764032958	Henco Bending tool Ø26	
PH-1632	05414764032958	Henco Pipe holder for diameters 16-20-26-32	

Product code	GTIN	Description
IM1426PRESS	05414764032958	Henco Guillotine cutter 14-26mm
KS26M	05414764032958	Henco Kalispeed (max. 500 rpm, clockwise) Ø26

**Image**

