


500-F16R-WZ: Henco Floor PE-Xc/AL/PE-Xc Ø16x2 m



Commercial information

Henco multilayer pipes offer all the **advantages** of metal and plastic:

- Aluminium inner core, seamlessly welded longitudinally
- 100 % oxygen-tight
- Minimal linear expansion coefficient comparable to metal
- Fully corrosion-resistant, including against chemical and electrochemical impacts
- Dampens noise, as typical of a plastic pipe
- Inner and outer pipe made of electron-beam cross-linked polyethylene
- High resistance to pressure and temperature
- Smooth surface: low pressure loss
- As light as a plastic pipe
- Flexible, easy to bend. The pipe retains its curved shape even in low temperatures

Basic unit dimensions

Height	16 mm
Length	1,000 mm
Width	16 mm
Net weight	0.100 kg

Certificates

Applications

Underfloor Heating

Solutions

Building installations, Industry, Underfloor heating, Utility

Technical characteristics

Material intermediate layer	Aluminium	Outer pipe diameter	16 Millimetre
Material outer layer	Plastic (expired)	Wall thickness	2 Millimetre
Glass-fibre reinforced	✗	Medium temperature (continuous)	- Degrees celsius 10 6 0
Diffusion-proof	✓	Max. medium temperature (momentarily)	60 Degrees celsius
Nominal diameter	DN 12	Max. operating pressure at 20 °C	6 Bar
System specific	✓	Max. operating pressure at max. medium temperature	6 Bar
Flexible	✓	Wall roughness	0.00 Millimetre 7
Suitable for surface mounting	✗	Expansion coefficient	0.02 Millimetre per metre Kelvin 5
Pipe colour	White	Min. bending radius	48 Millimetre
With mantle pipe	✗	Min. bending radius without tools	48 Millimetre
With heating cable	✗	Outer diameter mantle pipe	0 Millimetre
With thermal insulation	✗	Thickness of thermal insulation	0 Millimetre
SVGW certified	✗	Lambda value	0.43 Watt per metre Kelvin
Capped	✗	Outer diameter thermal insulation	0 Millimetre
UV resistant	✗	Outer width rectangular insulation	0 Millimetre
Halogen free	✓	Outer height rectangular insulation	0 Millimetre
DIN-CERTCO certificate	✗	Water content	0.11 Litre per metre 3
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✗		
Compliant with NF 545	✗		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		