



Features

- Provides the necessary UVB radiation for reptile habitats. Daylight colour temperature 6500K. This lamp emits UV-radiation, Avoid exposure.

Product Overview

Product name	F15W REPTISTAR UV-B 10%
Technology	Fluorescent
Cap/Base	G13
Fixture rating	Open
Colour temperature (K)	6500
Wattage (W)	15.00
Product EAN number	5410288007410

Data table

GENERAL DATA

Product name	F15W REPTISTAR UV-B 10%
Technology	Fluorescent
Cap/Base	G13
Fixture rating	Open
Operating temperature range (°C)	-15°C...+40°C

OPTICAL DATA

F15W REPTISTAR UV-B 10% 0000741

Ambient temperature for maximum luminous flux (°C)	25
--	----

Colour temperature (K)	6500
------------------------	------

Adjustable chromaticity	N
-------------------------	---

ELECTRICAL DATA

Wattage (W)	15.00
-------------	-------

Current (A)	0.310
-------------	-------

Primary Supply/Product voltage - min (V)	46.0
--	------

Control gear required	No
-----------------------	----

Drive current (mA)	310
--------------------	-----

PHYSICAL DATA

Nominal Product Length (mm)	450.0
-----------------------------	-------

Nominal Product Diameter (mm)	26
-------------------------------	----

Max. Length base to base (mm) - A	437.4
-----------------------------------	-------

Length base to pin Min-Max (mm) - B	442.1-444.5
-------------------------------------	-------------

Max. Lamp Length (mm) - C/L	451.6
-----------------------------	-------

Max. Lamp Diameter (mm) - D	28.0
-----------------------------	------

Weight (kg)	0.062
-------------	-------

PACKAGING

Single packaging type	Carton
-----------------------	--------

Product EAN number	5410288007410
--------------------	---------------

Packaging single width (cm)	2.7
-----------------------------	-----

Packaging single depth (cm)	2.7
-----------------------------	-----

DUN14 (outer)	15410288007417
---------------	----------------

Packaging outer length / height (cm)	70.1
--------------------------------------	------

SAFETY DATA

Lamp mercury content (mg)	2.80
---------------------------	------

Optimal operating condition (°C)	-15-40
----------------------------------	--------

Breakage cleaning instructions	Applicable
--------------------------------	------------

F15W REPTISTAR UV-B 10% 0000741

Special purpose lamp	Yes
Intended purpose	High UV Content (>2mW/klm)(Terrarium High UV lamps)
Dry applications use only	No
Suitable for household illumination	No
Safety message	Not suitable for household