


50-COMBI16: Henco Standard $\text{\O}16 \times 2$ combi 2x50m



Commercial information

The Henco Combi® consists of two Henco multilayer pipes, both equipped with a protective pipe. The two protective pipes are locally connected to each other, allowing you to roll off two pipes in a single motion. The locally perforated connections ensure that the two pipes can be easily separated. A red marking on one of the corrugated pipes indicates the supply pipe.

Certificates

KOMO, ATG, QB (CSTBat), DVGW Wasser, ETA, ÖVGW Wasser, SITAC, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, KIWA, SINTEF, WRAS, Bureau Veritas, RISE, AFNOR, PZH, STF, ACS, DNV-GL, Aenor, Sans 21003, Kontrol Biro, EMI

Applications

Potable water, Heating, Cooling, Compressed air, Demi Water, Sanitary





Solutions



Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material inner layer	Plastic	Number of layers	5
Quality class inner layer	PE-Xc	Outer pipe diameter	16 Millimetre
Material intermediate layer	Aluminium	Wall thickness	2 Millimetre
Material outer layer	Plastic	Medium temperature (continuous)	- Degrees celsius 10 7 0
Quality class outer layer	PE-Xc	Max. medium temperature (momentarily)	95 Degrees celsius
Glass-fibre reinforced	✘	Max. operating pressure at 20 °C	16 Bar
Diffusion-proof	✓	Max. operating pressure at max. medium temperature	16 Bar
Nominal diameter	DN 12	Wall roughness	0.00 Millimetre 7
System specific	✓	Expansion coefficient	0.02 Millimetre per metre Kelvin 5
Flexible	✘	Min. bending radius	48 Millimetre
Suitable for surface mounting	✓	Min. bending radius without tools	48 Millimetre
Pipe colour	Grey	Outer diameter mantle pipe	25.2 Millimetre
With mantle pipe	✓	Thickness of thermal insulation	0 Millimetre
With heating cable	✘	Lambda value	0.43 Watt per meter Kelvin
Colour outer sheath	Grey	Outer diameter thermal insulation	0 Millimetre
With thermal insulation	✘	Outer width rectangular insulation	0 Millimetre
SVGW certified	✘	Outer height rectangular insulation	0 Millimetre
Capped	✘	Water content	0.11 Litre per metre 3
UV resistant	✘		
Halogen free	✓		
DIN-CERTCO certificate	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✓		
Compliant with NF 545	✓		
KOMO certified	✓		
Type approval according to BBR/EKS	✘		

Related products

Product code	GTIN	Description	Image
IM1426PRESS	05414764034877	Henco Guillotine cutter 14-26mm	
PH-1632	05414764034877	Henco Pipe holder for diameters 16-20-26-32	
KS16M	05414764034877	Henco Kalispeed (max. 500 rpm, clockwise) Ø16	
KS-K	05414764034877	Henco Clickhandle for KS (Kalispeed)	

Product code	GTIN	Description	Image
PS-16	05414764034877	Henco Pipe straightener Ø16	
BI-1612	05414764034877	Henco Internal Bending spring 16x2 l=50	
TESTPLUG16	05414764034877	Henco Test cap for pipe Ø16	