


## Data Sheet | Item Number: 788-121

Accessories for relay modules; Operation status indicator: red; Nominal operating voltage range: 48 ... 60 VDC

<https://www.wago.com/788-121>



Similar to illustration

### Notes

Note Only required when using relays without integrated status indicator!

### Technical data

#### Operating Data

Nominal operating voltage	48 VDC
Operating voltage	48 ... 60 VDC
Current consumption at $U_N$	1.9 mA

#### Signaling

Status indicator	Red LED
------------------	---------

### Mechanical data

Mounting type	Pluggable module
---------------	------------------

### Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Fire load	0.027 MJ
Weight	1.7 g



**Commercial data**

Product Group	6 (INTERFACE ELECTRONIC)
PU (SPU)	50 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454550349
Customs tariff number	85318070000

**Product Classification**

UNSPSC	39122333
eCl@ss 10.0	27-37-16-92
eCl@ss 9.0	27-37-16-92
ETIM 9.0	EC002586
ETIM 10.0	EC002586
ECCN	NO US CLASSIFICATION

**Environmental Product Compliance**

CAS-No.	7439-92-1 79-94-7
REACH Candidate List Substance	2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	7(a)
SCIP notification number (Bulgaria)	b37affb3-7a63-4c08-b562-9c2aa4b1e704
SCIP notification number (Czech Republic)	e6884efa-4b07-4509-b20b-c1ccd6476458

**Downloads**




**Environmental Product Compliance**

<b>Compliance Search</b>	
Environmental Product Compliance 788-121	<a href="#">↓</a>

**Documentation**

<b>Bid Text</b>			
788-121	19.02.2019	xml 2.57 KB	<a href="#">↓</a>
788-121	20.02.2019	docx 15.13 KB	<a href="#">↓</a>

CAD/CAE-Data

CAD data	CAE data
2D/3D Models 788-121 	EPLAN Data Portal 788-121 
	WSCAD Universe 788-121 
	ZUKEN Portal 788-121 