

Specifications

Photo is representative

Eaton SC-2

Eaton Bussmann Series Class G fuse, SC, fast-acting, current limiting fuse, 2 A, rejection style fuse, interrupting rating of 100 kA at 600 Vac and 10 kA at 170 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series SC fuse
CATALOG NUMBER	SC-2
UPC	051712250023
PRODUCT LENGTH/DEPTH	1.31 in
PRODUCT HEIGHT	0.41 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.1 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant CE Marked
PRODUCT TYPE	Fuse



Powering Business Worldwide

Electrical rating

AMPERAGE RATING	2 A
INTERRUPT RATING	100 kAIC at 600 Vac 10 kAIC at 170 Vdc
VOLTAGE RATING	600 Vac, 170 Vdc

General information

CLASS	Class G
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Ferrule design, Type P

Physical details

PACKAGING TYPE	Standard
-----------------------	----------

Resources

CATALOGS	Low Voltage Branch Circuit Fuse Chapter Bussmann Full Line Catalog
COMPLIANCE INFORMATION	RoHS Search Tool
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - SC-2 Bussmann series Rejecting Fuses data sheet no. 1024
TECHNICAL DATA SHEETS	Bussmann series KRP-CL Class L fuse data sheet no.1016
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

