

## Data Sheet | Item Number: 2006-8401

Disconnect plug for carrier terminal blocks; for using a receptacle terminal block as a disconnect terminal block; orange

<https://www.wago.com/2006-8401>



Color: ■ orange

### Electrical data

#### Ratings per IEC/EN

Nominal voltage (III/3)	1500 V
Rated impulse withstand voltage (III / 3)	12 kV
Rated current	30 A

### Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	orange
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.039 MJ
Weight	3.2 g

### Environmental requirements

Continuous operating temperature	105 °C
----------------------------------	--------

#### Environmental Testing

Test specification: Railway applications – Rolling stock – Electronic equipment	DIN EN 50155 (VDE 0115-200):2022-06
Test procedure: Railway applications – Rolling stock equipment – Vibration and shock tests	DIN EN 61373 (VDE 0115-0106):2011-04
Spectrum/Mounting location	Service life test, Category 1, Class A/B
Functional test with noise-like oscillations	Test passed according to Section 8 of the standard
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 150 \text{ Hz}$
Acceleration	0.101g (highest test level used for all axes)
Test duration per axis	10 min.

## Environmental Testing

Test directions	X, Y and Z axes
Monitoring of contact faults and interruptions	Passed
Voltage drop measurement before and after each axis	Passed
Simulated service life test through increased levels of noise-like oscillations	Test passed according to Section 9 of the standard
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 150 \text{ Hz}$
Acceleration	0.572g (highest test level used for all axes)
Test duration per axis	5 h
Test directions	X, Y and Z axes
Extended testing: Monitoring of contact faults and interruptions	Passed
Extended testing: Voltage drop measurement before and after each axis	Passed
Shock test	Test passed according to Section 10 of the standard
Shock pulse form	Half sine
Acceleration	5g (highest test level used for all axes)
Shock duration	30 ms
Number of shocks (per axis)	3 pos. und 3 neg.
Test directions	X, Y and Z axes
Extended testing: Monitoring of contact faults and interruptions	Passed
Extended testing: Voltage drop measurement before and after each axis	Passed
Vibration and shock stress for rolling stock equipment	Passed

## Commercial data

Product Group	22 (TOPJOB S)
PU (SPU)	48 (12) pcs
Packaging type	Box
Country of origin	DE
GTIN	4050821372479
Customs tariff number	85366990990

## Product Classification

UNSPSC	39121421
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 10.0	EC002848
ECCN	NO US CLASSIFICATION

**Environmental Product Compliance**

RoHS Compliance Status Compliant, No Exemption

**Approvals / Certificates**

**General approvals**



Approval	Standard	Certificate Name
CSA CSA Group	C22.2 No. 158	1543858

**Declarations of conformity and manufacturer's declarations**



Approval	Standard	Certificate Name
Railway WAGO GmbH & Co. KG	-	Railway Ready

**Downloads**

**Environmental Product Compliance**

Compliance Search

Environmental Product Compliance 2006-8401	↓
--	---

**Documentation**

Bid Text

Item Number	Date	File Type / Size	Action
2006-8401	19.02.2019	xml 2.57 KB	↓
2006-8401	28.04.2017	doc 23.50 KB	↓

**CAD/CAE-Data**



CAD data

2D/3D Models 2006-8401	↓
---------------------------	---

CAE data

WSCAD Universe 2006-8401	↓
-----------------------------	---

**Installation Notes**



Carrier terminal block with disconnect plug (2006-8401) in operating position

Carrier terminal block with disconnect plug (2006-8401) in parked position

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: [www.wago.com](http://www.wago.com)