

149-142 30 graden specific configuration

Wall lamp | cube 10x10x10cm | black | 6W | 3000K | dim

Introduction

Purpose of this Document

This document provides information for 149-142 30 graden. During measurement, the product is used in a different mode where output power, colour temperature and/or beam angle are changed from factory standard. These adjustments can be made without altering the product and are designed to be set by the installer. In most cases, the options are set through switches on the product.

Results

| | |
|-------------------------------|---------|
| Total input power | 5.4 W |
| Correlated Colour Temperature | 3223 K |
| Total lumen output | 102 lm |
| Efficiency | 19 lm/W |


Electrical measurement details

Input Power

| | |
|--|---------|
| RMS Input voltage feed. V_{RMS} | 229 V |
| RMS Input current feed. I_{RMS} | 0.026 A |
| Total input power | 5.4 W |
| Frequency of input power | 50 Hz |
| Power factor | 0.92 |
| Displacement power factor | 0.93 |
| Total harmonic distortion of the current | 17.19% |
| Total harmonic distortion of the voltage | 2.64% |

Input Power Curve

Voltage - Current



Efficiency

Radiated power efficiency: 5.8%




Lumen efficiency: 19 lm/W



Harmonics

| | |
|---------------|-------|
| 3rd Harmonic | 8.89% |
| 5th Harmonic | 7.71% |
| 7th Harmonic | 4.41% |
| 9th Harmonic | 5.02% |
| 11th Harmonic | 4.8% |

Current Harmonics %




149-142 30 graden specific configuration

Colour measurement details


Total lumen output 102 lm
 Correlated Colour Temperature 3223 K
 Colour coordinates CIE 1931 (x;y) = (0.424;0.403)
 Colour deviation from BBL Duv = 0.0015

TM30-18 Colour Fidelity Index R_f 87.1
 TM30-18 Colour Gamut Index R_g 96.6
 Colour Rendering Index (Ra) CRI 84.6
 Colour Rendering Index. (red component) $R_9 = 11.5$


Colour Quality Scale CQS = 84.3
 Television Lighting Consistency Index TLCI = 72




Relative spectral power distribution



TM30 details




TM30 Colour vectors per hue bin




TM30 Colour distortion


| Hue Bin | R_f | Shifts (%) | |
|---------|-------|------------|------|
| | | Chroma | Hue |
| C1 | 82 | -10% | -1% |
| C2 | 84 | -7% | 6% |
| C3 | 81 | -3% | 9% |
| C4 | 90 | 1% | 6% |
| C5 | 93 | 3% | 4% |
| C6 | 94 | 3% | -2% |
| C7 | 89 | -2% | -7% |
| C8 | 95 | -2% | -2% |
| C9 | 92 | -5% | 1% |
| C10 | 87 | -5% | 6% |
| C11 | 85 | -1% | 10% |
| C12 | 89 | 6% | 1% |
| C13 | 90 | 4% | -6% |
| C14 | 83 | 4% | -14% |
| C15 | 81 | -2% | -12% |
| C16 | 81 | -7% | -14% |



TM30-18 R_f -values per reference colour




TM30-18 R_f -values per hue bin




TM30 Chroma shift

Colour Quality details



Colour Rendering Index



Colour Quality Scale