

Specifications



Eaton CCP2SL-3-30CF

Eaton Bussmann series CCP UL98 fusible disconnect, Finger Safe, Lock-On provision, 600 Vac, 125 Vdc, 225A, UL98 fusible disconnect, Three-pole, 200 kA - CCP2SL-3-30CF

General specifications

PRODUCT NAME	Eaton Bussmann series CCP UL98 fusible disconnect
CATALOG NUMBER	CCP2SL-3-30CF
UPC	051712709910
PRODUCT LENGTH/DEPTH	2.9 in
PRODUCT HEIGHT	3.7 in
PRODUCT WIDTH	0.3 in
PRODUCT WEIGHT	3.7 lb
WARRANTY	Not Applicable
COMPLIANCES	CCC Marked
CERTIFICATIONS	Contact Manufacturer
PRODUCT TYPE	UL98 fusible disconnect

Electrical rating

AMPERAGE RATING	225 A
SHORT-CIRCUIT RATING	200 kAIC
VOLTAGE RATING	600 Vac, 125 Vdc

General information

SPECIAL FEATURES Finger Safe, Lock-On provision

SUITABLE FOR FUSES TCF6 to TCF30
TCF1RN to TCF30RN
FCF1RN to FCF30RN

Physical details

NUMBER OF POLES Three-pole

Resources

CATALOGS [CCP2SL-3-30CF~CCP2 3P 30A CF W/ SIDE HandM LEFT](#)

[Bussmann series complete full line catalog no. 1007](#)

DECLARATIONS OF CONFORMITY [Eaton Bussmann EU Declaration of conformity 93-68-EEC2512](#)

SPECIFICATIONS AND DATASHEETS [Eaton Specification Sheet - CCP2SL-3-30CF](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

