

Specifications

Eaton 207247

Eaton Moeller® series T5B Main switch, T5B, 63 A, surface mounting, 4 contact unit(s), 6 pole, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position

General specifications

| | |
|-----------------------------|---|
| PRODUCT NAME | Eaton Moeller® series T5B Main switch |
| CATALOG NUMBER | 207247 |
| MODEL CODE | T5B-4-15682/I4/SVB-SW |
| EAN | 4015082072476 |
| PRODUCT LENGTH/DEPTH | 240 mm |
| PRODUCT HEIGHT | 204 mm |
| PRODUCT WIDTH | 160 mm |
| PRODUCT WEIGHT | 1.49 kg |
| WARRANTY | Not Applicable |
| CERTIFICATIONS | UL Listed CSA Certified VDE 0660 UL CE UL 60947-4-1 IEC/EN 60947-3 CSA-C22.2 No. 94 UL Category Control No.: NLRV UL File No.: E36332 CSA CSA-C22.2 No. 60947-4-1-14 IEC/EN 60204 CSA Class No.: 3211-05 CSA File No.: 012528 IEC/EN 60947 |
| CATALOG NOTES | Rated Short-time Withstand Current (Icw) for a time of 1 second |
| GLOBAL CATALOG | 207247 |



Powering Business Worldwide

Product specifications

| | |
|---|--|
| PRODUCT CATEGORY | Main switch |
| FEATURES | Version as maintenance- /service switch Version as main switch |
| ACTUATOR COLOR | Black |
| 10.10 TEMPERATURE RISE | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 SHORT-CIRCUIT RATING | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 ELECTROMAGNETIC COMPATIBILITY | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 MECHANICAL FUNCTION | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |
| 10.2.2 CORROSION RESISTANCE | Meets the product standard's requirements. |
| 10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES | Meets the product standard's requirements. |
| 10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT | Meets the product standard's requirements. |
| 10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS | Meets the product standard's requirements. |
| 10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION | UV resistance only in connection with protective shield. |
| 10.2.5 LIFTING | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 MECHANICAL IMPACT | Does not apply, since the entire switchgear needs to be evaluated. |

| | |
|---|--|
| 10.2.7 INSCRIPTIONS | Meets the product standard's requirements. |
| 10.3 DEGREE OF PROTECTION OF ASSEMBLIES | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 CLEARANCES AND CREEPAGE DISTANCES | Meets the product standard's requirements. |
| 10.5 PROTECTION AGAINST ELECTRIC SHOCK | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS | Is the panel builder's responsibility. |
| 10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS | Is the panel builder's responsibility. |
| 10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH | Is the panel builder's responsibility. |
| 10.9.3 IMPULSE WITHSTAND VOLTAGE | Is the panel builder's responsibility. |
| 10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL | Is the panel builder's responsibility. |
| FITTED WITH: | Black rotary handle and locking ring |
| OPERATING FREQUENCY | 1200 Operations/h |
| POLLUTION DEGREE | 3 |
| CLIMATIC PROOFING | Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78 |
| RATED IMPULSE WITHSTAND VOLTAGE (UIMP) | 6000 V AC |
| RATED OPERATIONAL POWER STAR-DELTA AT 500 V, 50 HZ | 37 kW |
| RATED OPERATIONAL POWER STAR-DELTA AT 690 V, 50 HZ | 22 kW |
| RATED PERMANENT CURRENT AT AC-21, 400 V | 63 A |
| RATED PERMANENT CURRENT AT AC-23, 400 V | 63 A |
| RATED UNINTERRUPTED CURRENT (IU) | 63 A |

| | |
|---|--------------------------------------|
| STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS | 0 W |
| SWITCHING ANGLE | 90 ° |
| SWITCHING POWER AT 400 V | 30 kW |
| VOLTAGE PER CONTACT PAIR IN SERIES | 60 V |
| RATED OPERATIONAL POWER AT AC-3, 500 V, 50 HZ | 22 kW |
| DEVICE CONSTRUCTION | Complete device in housing |
| RATED SHORT-TIME WITHSTAND CURRENT (ICW) | 1,3 kA, Contacts, 1 second 1.3 kA |
| ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT | Screw connection |
| DESIGN | 15682 |
| MOUNTING POSITION | As required |
| ACTUATOR TYPE | Door coupling rotary drive |
| AMBIENT OPERATING TEMPERATURE - MAX | 40 °C |
| AMBIENT OPERATING TEMPERATURE - MIN | -25 °C |
| AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX | 40 °C |
| AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN | -25 °C |
| ASSIGNED MOTOR POWER AT 115/120 V, 60 HZ, 1-PHASE | 3 HP |
| ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 1-PHASE | 7.5 HP |
| ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE | 15 HP |
| ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE | 10 HP |
| ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 3-PHASE | 15 HP |

| | |
|--|--|
| ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE | 40 HP |
| ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE | 40 HP |
| EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID | 4.5 W |
| HEAT DISSIPATION CAPACITY PDISS | 0 W |
| HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID | 4.5 W |
| NUMBER OF AUXILIARY CONTACTS (CHANGE- OVER CONTACTS) | 0 |
| NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS) | 1 |
| RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ) | 2 kA |
| OVERVOLTAGE CATEGORY | III |
| CONTROL CIRCUIT RELIABILITY | 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA) |
| DEGREE OF PROTECTION (FRONT SIDE) | IP65 |
| NUMBER OF POLES | 6 |
| MOUNTING METHOD | Surface mounting |
| DEGREE OF PROTECTION | NEMA 12 |
| SUITABLE FOR | Ground mounting Branch circuits, suitable as motor disconnect, (UL/CSA) |
| LOCKING FACILITY | Lockable in the 0 (Off) position |
| FUNCTIONS | Interlockable STOP function |
| NUMBER OF SWITCHES | 1 |
| SAFE ISOLATION | 440 V AC, Between the contacts, According to EN 61140 |
| SCREW SIZE | M6, Terminal screw |
| SHOCK RESISTANCE | 15 g, Mechanical, |

| | |
|--|---|
| | According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms |
| LIFESPAN, MECHANICAL | 500,000 Operations |
| LOAD RATING | 1.6 x I _e (with intermittent operation class 12, 40 % duty factor) 1.3 x I _e (with intermittent operation class 12, 60 % duty factor) 2 x I _e (with intermittent operation class 12, 25 % duty factor) |
| TERMINAL CAPACITY | 1 x (1 - 25) mm ² , flexible with ferrules to DIN 46228 2 x (1.5 - 10) mm ² , flexible with ferrule to DIN 46228 12 - 4 AWG, solid or flexible with ferrule 2 x (2.5 - 16) mm ² , solid or stranded 1 x (2.5 - 35) mm ² , solid or stranded |
| SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE) | 63 A, Rated uninterrupted current max. (UL/CSA) |
| SAFETY PARAMETER (EN ISO 13849-1) | B10d values as per EN ISO 13849-1, table C.1 |
| NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS) | 1 |
| NUMBER OF CONTACT UNITS | 4 |
| NUMBER OF CONTACTS IN SERIES AT DC-23A, 120 V | 3 |
| NUMBER OF CONTACTS IN SERIES AT DC-23A, 24 V | 1 |
| NUMBER OF CONTACTS IN SERIES AT DC-23A, 240 V | 6 |
| NUMBER OF CONTACTS IN SERIES AT DC-23A, 48 V | 2 |
| NUMBER OF CONTACTS IN SERIES AT DC-23A, 60 V | 3 |
| RATED BREAKING CAPACITY AT 220/230 V (COS PHI TO IEC 60947-3) | 520 A |
| RATED BREAKING CAPACITY AT 400/415 V (COS PHI TO IEC 60947-3) | 600 A |

| | |
|--|---|
| RATED BREAKING CAPACITY AT 500 V (COS PHI TO IEC 60947-3) | 480 A |
| RATED BREAKING CAPACITY AT 660/690 V (COS PHI TO IEC 60947-3) | 340 A |
| RATED MAKING CAPACITY UP TO 690 V (COS PHI TO IEC/EN 60947-3) | 800 A |
| RATED OPERATING VOLTAGE (UE) - MAX | 690 V |
| RATED OPERATING VOLTAGE (UE) - MIN | 690 V |
| RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX | 690 V |
| SHORT-CIRCUIT CURRENT RATING (HIGH FAULT) | 100 A, Class J, max. Fuse, SCCR (UL/CSA) 10 kA, SCCR (UL/CSA) |
| SHORT-CIRCUIT PROTECTION RATING | 80 A gG/gL, Fuse, Contacts |
| RATED OPERATIONAL CURRENT (IE) AT AC-21, 440 V | 63 A |
| RATED OPERATIONAL CURRENT (IE) AT AC-23A, 230 V | 63 A |
| RATED OPERATIONAL CURRENT (IE) AT AC-23A, 400 V, 415 V | 63 A |
| RATED OPERATIONAL CURRENT (IE) AT AC-23A, 500 V | 33 A |
| RATED OPERATIONAL CURRENT (IE) AT AC-23A, 690 V | 23.8 A |
| RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V | 51 A |
| RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V | 41 A |
| RATED OPERATIONAL CURRENT (IE) AT AC-3, 500 V | 33 A |
| RATED OPERATIONAL CURRENT (IE) AT AC-3, 660 V, 690 V | 17 A |
| RATED OPERATIONAL | 63 A |

| | |
|--|---------|
| CURRENT (IE) AT DC-1, LOAD-BREAK SWITCHES L/R = 1 MS | |
| RATED OPERATIONAL CURRENT (IE) AT DC-13, CONTROL SWITCHES L/R = 50 MS | 25 A |
| RATED OPERATIONAL CURRENT (IE) AT DC-23A, 120 V | 25 A |
| RATED OPERATIONAL CURRENT (IE) AT DC-23A, 24 V | 50 A |
| RATED OPERATIONAL CURRENT (IE) AT DC-23A, 240 V | 20 A |
| RATED OPERATIONAL CURRENT (IE) AT DC-23A, 48 V | 50 A |
| RATED OPERATIONAL CURRENT (IE) AT DC-23A, 60 V | 50 A |
| RATED OPERATIONAL CURRENT (IE) STAR- DELTA AT AC-3, 220/230 V | 63 A |
| RATED OPERATIONAL CURRENT (IE) STAR- DELTA AT AC-3, 380/400 V | 63 A |
| RATED OPERATIONAL CURRENT (IE) STAR- DELTA AT AC-3, 500 V | 57.2 A |
| RATED OPERATIONAL CURRENT (IE) STAR- DELTA AT AC-3, 690 V | 29.4 A |
| RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) | 63 A |
| RATED OPERATIONAL POWER AT AC-23A, 220/230 V, 50 HZ | 18.5 kW |
| RATED OPERATIONAL POWER AT AC-23A, 400 V, 50 HZ | 30 kW |
| RATED OPERATIONAL POWER AT AC-23A, 500 V, 50 HZ | 22 kW |
| RATED OPERATIONAL POWER AT AC-23A, 690 V, 50 HZ | 22 kW |
| RATED OPERATIONAL | 22 kW |

| | |
|---|---|
| POWER AT AC-3, 380/400 V, 50 HZ | |
| RATED OPERATIONAL POWER AT AC-3, 415 V, 50 HZ | 22 kW |
| RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ | 15 kW |
| RATED OPERATIONAL POWER STAR-DELTA AT 220/230 V, 50 HZ | 18.5 kW |
| RATED OPERATIONAL POWER STAR-DELTA AT 380/400 V, 50 HZ | 30 kW |
| TIGHTENING TORQUE | 35.4 lb-in, Screw terminals 4 Nm, Screw terminals |
| UNINTERRUPTED CURRENT | Rated uninterrupted current I _u is specified for max. cross-section. |
| RATED SWITCHING CAPACITY | 10 HP at 240 V AC, single-phase 15 HP at 200 V AC, three-phase 15 HP at 240 V AC, three-phase 3 HP at 120 V AC, single-phase 40 HP at 480 V AC, three-phase 40 HP at 600 V AC, three-phase 7.5 HP at 200 V AC, single-phase |

Resources

BROCHURES

[Brochure - T Rotary Cam switch and P Switch-disconnector](#)

CATALOGS

[P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN](#)

DECLARATIONS OF CONFORMITY

[DA-DC-00004925.pdf](#) [DA-DC-00004897.pdf](#)

DRAWINGS

[eaton-rotary-switches-padlock-t0-main-switch-dimensions.eps](#)
[eaton-rotary-switches-surface-mounting-t5b-main-switch-dimensions-002.eps](#)
[eaton-general-totally-insulated-t0-main-switch-symbol.eps](#)

| | |
|-------------------------------|---|
| | eaton-rotary-switches-t0-main-switch-symbol.eps eaton-general-switch-t0-main-switch-symbol.eps eaton-rotary-switches-surface-mounting-t0-main-switch-3d-drawing.eps |
| ECAD MODEL | ETN.207247.edz |
| INSTALLATION INSTRUCTIONS | IL03801009Z |
| INSTALLATION VIDEOS | Eaton's P Switch-disconnectors used in a factory |
| MCAD MODEL | DA-CD-bauform13 DA-CS-bauform13 |
| PRODUCT NOTIFICATIONS | MZ008005ZU_Orderform_Customized_Switch.pdf MZ008006ZU_Orderform_Customized_Switch.pdf |
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - 207247 |
| WIRING DIAGRAMS | eaton-rotary-switches-switch-t0-main-switch-wiring-diagram-003.eps |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

