

RF receiver, potential free, 1 changeover contact, flush mounting

410-00332

CE

4 year warranty

This flush-mounted receiver allows switching an electrical device ON and OFF using a wireless Easywave button or a wired button. This receiver has a potential-free changeover relay contact, suitable to control devices such as a doorbell or a dimmer.

It can receive signals from a Niko Easywave hand-held transmitter and/or wireless switch. The receiver can be installed behind a Niko blind plate or push button in the colour of your choice. Please note that the combination with the push button requires a wall mounting box with an installation depth of minimum 50 mm.

Up to 32 transmission codes can be programmed into the receiver. The receiver is equipped with either 1-button operation (ON/OFF, DEAD MAN, TIMER) or 2-button operation (ON/OFF, LOGIC).



Technical data

RF receiver, potential free, 1 changeover contact, flush mounting

- Radiated power: 6.38 mW
- Modulation: FSK
- Input: 1 external push button
- Output: 1 potential-free relay contact (changeover)
- Power consumption (stand-by): 0.3 W
- Power consumption without load: 0.8 W
- Maximum contact load:
- Not compatible with Niko Home Control (wireless bridge or wireless smart hub)
- Input voltage: 230 Vac
- Maximum MCB rating: -10
- Wireless communication protocol: Easywave
- Protection degree standalone: IP20
- Dimensions (HxWxD): 43 mm x 42 mm x 17.5 mm
- Marking: CE

Wiring diagram

