



Features

- Ceiling recessed LED Linear luminaire with Louvre +MicroPrismatic Optic, Dimensions: 1154mm x 90mm x 91mm, Direct, White Body, SylSmart Standalone capable, Electric Class 1, Tunable White LED (3000-6000K), 2900lm, 31W, 94lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse), Low LED Flicker (+/-5%), UGR<19, L90B10 at 50,000 hours, Glow Wire Test 850°C, Can be covered with building insulation of Glass Wool type.



Product Overview

Product name	RANA LINEAR R 3KLM TW LOUV+PRI SSC01 WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Fixture luminous flux (lm)	2900
Luminaire efficacy (lm/W)	94
Light colour	Tuneable White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 17
Photobiological Risk Group	RG1
Total power consumption (W)	31
Electrical protection	Class I
Control gear type	Electronic ballast
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07

RANA LINEAR R 3KLM TW LOUV+PRI SSC01 WHITE 0052485


Product EAN number

5410288524856

Warranty

5 years

Photometry



Technical drawings

