

## SHP-S TwinArc

*SHP-S 150W TWINARC E40 SLV*  
0020740



### Product features


- Range of high pressure sodium lamps with double arc tube construction, - Dual arc tube design guarantees immediate re-strike after a power interruption, - Double lamp life and reduced occurrence of early failures, -Ideal for applications which are difficult to access, or where maintenance is expensive, -Perfect for tunnels, airports, military installations, harbours and industrial sites



## PRODUCT OVERVIEW

Product name	SHP-S 150W TWINARC E40 SLV
Technology	HID
Watt (Rated) (W)	155
Cap/Base	E40
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	Logistics & Industry
ETIM Class	EC000821
E-number FI	4845534
E-number SE	8358108
E-number Norway	3800725
Useful luminous flux (Fuse)	16580
Luminous flux (lm)	16580
Colour temperature (K)	2050
CRI (Ra)	20
Colour Variation Initial (SDCM)	N/A
Photobiological Risk Group	Not applicable
Wattage (W)	155
Dimmable	No
Dimming method	Mains: leading / trailing edge
Average life (Nominal) (h)	55000
Product EAN number	5410288207407

## PHOTOMETRY




## TECHNICAL DRAWINGS

## SHP-S TwinArc

*SHP-S 150W TWINARC E40 SLV*

0020740



SHP	50W	70W	100W	150W	250W	400W
L	165	165	178	227	227	292
D	72	72	78	91	91	122