

UFH-P18-GP18: Gypsum fibreboard 18mm, round milling for RENO12 system



Commercial information

UFH-P18-GP18 is a 18 mm gypsum fibreboard with round milling for the RENO12 system.

Basic unit dimensions

| | |
|------------|----------|
| Height | 18 mm |
| Length | 1,000 mm |
| Width | 600 mm |
| Net weight | 9.000 kg |

Certificates

Applications

Heating, Cooling, Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Utility

Technical characteristics

| | | | |
|--|-------|-----------|-----------------------------|
| Edge finishing long side | Other | Length | 1000 Millimetre |
| Edge finishing head end | Other | Width | 600 Millimetre |
| Colour visible surface | White | Thickness | 18 Millimetre |
| Suitable for wall mounting | ✘ | Weight | 9 Kilogram per square metre |
| Suitable for floor | ✓ | | |
| Suitable for ceiling mounting | ✘ | | |
| Suitable for damp space | ✓ | | |
| With insulation | ✘ | | |
| Fire retardant impregnated | ✘ | | |
| Suitable as plasterboard | ✘ | | |
| With perforation | ✘ | | |
| With decorative finish | ✘ | | |
| Lead insert | ✘ | | |
| Bendable | ✘ | | |
| Suitable for fire protection of load-bearing constructions | ✘ | | |
| Fixing | ✘ | | |
| Suitable for outdoor application | ✘ | | |
| Suitable for protection from radiation | ✘ | | |
| Factory bent board | ✘ | | |
| Glass-fibre reinforced | ✘ | | |
| Fleece reinforced | ✘ | | |