



## Features

- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- 15,000 hours average rated life


## Product Overview

Product name	ToLEDo GLS V9 1920LM 827 E27 SL
Technology	LED
Lamp shape	Pear-shape
Cap/Base	E27
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4741184
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	150
Photobiological Risk Group	RG0
Wattage (W)	16
Dimmable	No
Housing colour	White

## ToLEDo GLS V9 1920LM 827 E27 SL 0030041

IP rating	IP20
Product EAN number	5410288300412
Warranty	3 years
Useful luminous flux (#use)	1920

### Technical drawings



### Data table

#### GENERAL DATA

Product name	ToLEDo GLS V9 1920LM 827 E27 SL
Technology	LED
Lamp shape	Pear-shape
Cap/Base	E27
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4741184

ToLEDo GLS V9 1920LM 827 E27 SL  
0030041

Warranty	3 years
----------	---------

## OPTICAL DATA

Useful luminous flux (#use)	1920
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	150
Photobiological Risk Group	RG0

## ELECTRICAL DATA

Wattage (W)	16
Equivalent watt (W)	120
Primary Supply/Product voltage - min (V)	230
Primary Supply/Product voltage - max (V)	230
Control gear required	No
No. Of switching cycles before premature failures	>50000
Dimmable	No
Drive current (mA)	130
Inrush Current (A)	7
Inrush Duration (µs)	420
Lamp Energy Label (class)	E
Nominal Frequency (Hz)	50/60Hz

## LIFETIME DATA

Lifespan L70 B50	15000
Average life (Rated) (h)	15000

## PHYSICAL DATA

Housing colour	White
IP rating	IP20

ToLEDo GLS V9 1920LM 827 E27 SL  
0030041

Nominal Product Height (mm)	128
Nominal Product Diameter (mm)	68
Weight (kg)	0.069

## PACKAGING

Product EAN number	5410288300412
Packaging single length / height (cm)	6.9
Packaging single width (cm)	6.9
Packaging single depth (cm)	13.3
DUN14 (outer)	15410288300419
Units per outer package	6
Packaging outer length / height (cm)	21.5
Packaging outer width (cm)	14.5
Packaging outer depth (cm)	14.3

## SAFETY DATA

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

# SYLVANIA

ToLEDo GLS V9 1920LM 827 E27 SL  
0030041

## Energy label



0030041




**16**  
kWh/1000h



2019/2015



0030041



**16**  
kWh/1000h



2019/2015