

## **UFH-0605MDK08-03L:** 8-groups man. comp,flow meter 0-3L,therm.,washer and air vent 8x



Commercial information

Composite manifold for both housing and utility buildings. It is compact in construction and has adaptable fixing brackets, it therefore allows smooth installation. This manifold is equipped with flowmeters, control valves for each circuit. Outlets are connected to eurocone 3/4".

Certificates

**Applications** 

Heating, Cooling, Underfloor Heating

**Solutions** 

Building installations, Underfloor heating, Industry, Utility



## **Technical characteristics**

Connection type primary side	2-pipe	Outer pipe diameter primary connection	32 Millimetre
Suitable for cooling	✓	Medium temperature (continuous)	0 60 Degrees celsius
Material	Plastic	Max. operating pressure	6 Bar
Position primary connection	Left/right	Max. number of expansion groups	15
Primary connection	Internal thread cylindrical BSPT-Rp (ISO 7-1 / EN 10226-1)	Number of groups secondary	8
Nominal diameter primary connection	1 inch (25)	Outer pipe diameter secondary	12 20 Millimetre
With valves on primary connection	×	Flow-through capacity	0 5 Litre per hour
With mixing valve	×	Min. pressure difference secondary flow/return	0 Kilo Pascal
Expandable	✓	Width	99 Millimetre
Multi-zone manifold	×	Height	335 Millimetre
With temperature limit	×	Depth	518 Millimetre
With non-return valve	×		
With circulation pump	×		
Article compression class	PN 6		
With controller	×		
Hydraulic balance control	None		
Volume flow measurement	Analogue		
With thermometer	✔		
Temperature measurement supply	Analogue		
Temperature measurement return	Analogue		
With de-aeration	✓		
With pressure gauge	×		
Secondary connection	Euroconus standardless		
Nominal diameter secondary connection	3/4 inch (20)		
Closable groups	✓		
With flow-through indicator	✓		
With thermal actuator	×		
With wall-mounting bracket	✓		
With casing	×		

## **Related products**

Product code UFH-CAB-O615Z	<b>GTIN</b> 05414764418608	<b>Description</b> Henco Surface mount cabinet backless RAL9016 internal width 615MM	Image
UFH-CAB-O615	05414764418608	Henco Surface mount cabinet RAL9016 internal width 615MM	
UFH-CAB-I715	05414764418608	Henco Recessed manifold cabinet RAL9016 internal width 715MM	

