

Splashproof signalling device with transparent lens and LEDs (Led colour: red), white

700-38100



250 Vac



4 year warranty

This surface-mounting signalling device is equipped with a transparent cover and LEDs (Led colour: red). It is designed to be mounted in a splashproof mounting box. This device is extremely well-suited for use in damp areas and in ammonia-rich environments. Colour: transparent white

- all connections terminals are located at the top of the base:

Technical data

Splashproof signalling device with transparent lens and LEDs (Led colour: red), white.

- Colour: white
- Colour RAL (approximately): 7035
- Colour NCS (approximately): NCS S 1502-B
- Surface treatment: coloured in mass
- Number of lenses: 0
- Led colour: red
- Number of mechanisms: 1
- Markings on the flush-mounting frame: indelibly indicated at the rear side: terminals
- Hermetic seal: the function is designed to be mounted in a splashproof mounting box. The function has an integral closure and is hermetically sealed onto the appropriate box (to be ordered separately)
- Chemical resistance: tested and approved for use in environments with ammonia levels up to 20 ppm
- Protection degree: IP55 for the combination of a function and a splashproof mounting box
- Impact resistance: the combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Certification marks: CEBEC
- Marking: CE

