



### Features

- Ceiling Recessed LED Linear luminaire (lay-in), with Louvre + MPO diffuser, Direct Light Distribution, Luminaire Dimensions: 1196x296x52mm, Sylvania White body colour, IP20, IK07, Constant Current, Low LED flicker (+/-5%), Warm White (3000K), LED Colour Temperature, 3572lm, 30W, 119lm/W, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, UGR<18, Luminance at 65° < 3000 cd/m<sup>2</sup>, Lifespan: 96,000 hours L80B20, Glow Wire Test 850°C, Quick and easy electrical connection with direct access to push-connectors on top, 2 x metallic safety cables (1.5m) included, the luminaire can be covered with building insulation of Glass Wool type.


### Product Overview

<b>Product name</b>	RANA NEO 3500LM REC 1200x300 830 CC 1L WHITE
<b>Technology</b>	LED (3 SDCM)
<b>Cap/Base</b>	N/A
<b>Housing</b>	Steel
<b>Mount</b>	Ceiling recessed mounting
<b>Fixture luminous flux (lm)</b>	3572
<b>Luminaire efficacy (lm/W)</b>	119
<b>Colour temperature (K)</b>	3000
<b>Light colour</b>	Warm White
<b>CRI (Ra)</b>	80
<b>Colour Variation Initial (SDCM)</b>	3
<b>Glare control</b>	< 18
<b>Photobiological Risk Group</b>	RG0
<b>Total power consumption (W)</b>	30
<b>Electrical protection</b>	Class I
<b>Control gear type</b>	LED driver constant current
<b>LED Flickering Rate</b>	Ultra low (5% or less)


## RANA NEO 3500LM REC 1200x300 830 CC 1L WHITE 0052588

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288525884
Warranty	5 years

### Photometry



### Technical drawings



### Data table

#### GENERAL DATA

## RANA NEO 3500LM REC 1200x300 830 CC 1L WHITE 0052588

Product name	RANA NEO 3500LM REC 1200x300 830 CC 1L WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Performance ambient temperature Tq (°C)	25
Warranty	5 years

### OPTICAL DATA

Fixture luminous flux (lm)	3572
Luminaire efficacy (lm/W)	119
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 18
Photobiological Risk Group	RG0

### ELECTRICAL DATA

Total power consumption (W)	30
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.97
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Drive current (mA)	300
Inrush Current (A)	5.5
Inrush Duration (µs)	20
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz

## RANA NEO 3500LM REC 1200x300 830 CC 1L WHITE 0052588

LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	41
Max. products per 20A B Breaker	82

### LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B20	96000

### PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1196
Nominal Product Width (mm)	296
Weight (kg)	5.5

### PACKAGING

Single packaging type	Carton
Product EAN number	5410288525884
Packaging single width (cm)	6.5
Packaging single depth (cm)	32.0
DUN14 (outer)	05410288525884
Packaging outer length / height (cm)	124.5

### SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No