

# Specifications

Photo is representative

## Eaton 064978

Eaton Moeller® series P1 Main switch, P1, 32 A, rear mounting, 3 pole + N, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position

### General specifications

|                             |   |
|-----------------------------|---|
| <b>PRODUCT NAME</b>         | Eaton Moeller® series P1 Main switch  |
| <b>CATALOG NUMBER</b>       | 064978  |
| <b>MODEL CODE</b>           | P1-32/V/SVB-SW/N/HI11   |
| <b>EAN</b>                  | 4015080649786   |
| <b>PRODUCT LENGTH/DEPTH</b> | 90 mm   |
| <b>PRODUCT HEIGHT</b>       | 70 mm   |
| <b>PRODUCT WIDTH</b>        | 78 mm   |
| <b>PRODUCT WEIGHT</b>       | 0.287 kg  |
| <b>WARRANTY</b>             | Not Applicable  |
| <b>CERTIFICATIONS</b>       | IEC/EN 60947<br>IEC/EN 60947-3<br>VDE 0660<br>UL<br>UL 60947-4-1<br>CSA File No.: 012528<br>IEC/EN 60204<br>CSA Class No.: 3211-05<br>CSA-C22.2 No. 60947-4-1-14<br>UL Category Control No.: NLRV<br>UL File No.: E36332<br>CE<br>CSA<br>CSA-C22.2 No. 94 |
| <b>CATALOG NOTES</b>        | Rated Short-time Withstand Current (Icw) for a time of 1 second   |
| <b>GLOBAL CATALOG</b>       | 064978  |
| <b>PRODUCT TYPE</b>         | Main switch   |



Powering Business Worldwide

## Product specifications

|   |  |
|---|--|
| <b>PRODUCT CATEGORY</b>   | Main switch  |
| <b>FEATURES</b>   | Version as maintenance-<br>/service switch<br>Version as main switch   |
| <b>ACTUATOR COLOR</b>   | Black  |
| <b>10.10 TEMPERATURE RISE</b>   | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| <b>10.11 SHORT-CIRCUIT RATING</b>   | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.13 MECHANICAL FUNCTION</b>  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>10.2.2 CORROSION RESISTANCE</b>  | Meets the product standard's requirements.   |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.   |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.   |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.   |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>                                 | UV resistance only in connection with protective shield.   |
| <b>10.2.5 LIFTING</b>   | Does not apply, since the entire switchgear needs to be evaluated.   |
| <b>10.2.6 MECHANICAL IMPACT</b>   | Does not apply, since the entire switchgear needs to be evaluated.   |
| <b>10.2.7 INSCRIPTIONS</b>  | Meets the product standard's requirements.   |
| <b>10.3 DEGREE OF</b>   | Does not apply, since the  |

|   |  |
|---|--|
| <b>PROTECTION OF ASSEMBLIES</b>                                 | entire switchgear needs to be evaluated.                                       |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>                   | Meets the product standard's requirements.                                     |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                   | Does not apply, since the entire switchgear needs to be evaluated.             |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>   | Does not apply, since the entire switchgear needs to be evaluated.             |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>        | Is the panel builder's responsibility.   |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                 | Is the panel builder's responsibility.   |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                 | Is the panel builder's responsibility.   |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                         | Is the panel builder's responsibility.   |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b> | Is the panel builder's responsibility.   |
| <b>FITTED WITH:</b>   | Black rotary handle and locking ring   |
| <b>OPERATING FREQUENCY</b>                                      | 1200 Operations/h  |
| <b>POLLUTION DEGREE</b>   | 3  |
| <b>CLIMATIC PROOFING</b>  | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30 |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>                   | 6000 V AC  |
| <b>RATED PERMANENT CURRENT AT AC-21, 400 V</b>                  | 32 A   |
| <b>RATED PERMANENT CURRENT AT AC-23, 400 V</b>                  | 32 A   |
| <b>RATED UNINTERRUPTED CURRENT (IU)</b>                         | 32 A   |
| <b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>       | 0 W  |
| <b>SWITCHING POWER AT 400 V</b>                                 | 15 kW  |
| <b>RATED OPERATIONAL POWER AT AC-3, 500 V, 50 HZ</b>            | 18.5 kW  |
| <b>DEVICE CONSTRUCTION</b>                                      | Built-in device fixed built-in technique                                       |

|  |                                      |
|--|--------------------------------------|
| <b>RATED SHORT-TIME WITHSTAND CURRENT (ICW)</b>            | 0.64 kA<br>640 A, Contacts, 1 second |
| <b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b>          | Screw connection                     |
| <b>MOUNTING POSITION</b>                                   | As required                          |
| <b>ACTUATOR TYPE</b>                                       | Door coupling rotary drive           |
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b>                 | 50 °C                                |
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b>                 | -25 °C                               |
| <b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b>      | 40 °C                                |
| <b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b>      | -25 °C                               |
| <b>ASSIGNED MOTOR POWER AT 115/120 V, 60 HZ, 1-PHASE</b>   | 1 HP                                 |
| <b>ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 1-PHASE</b>   | 2 HP                                 |
| <b>ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE</b>   | 3 HP                                 |
| <b>ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE</b>   | 3 HP                                 |
| <b>ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 3-PHASE</b>   | 7.5 HP                               |
| <b>ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE</b>   | 10 HP                                |
| <b>ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE</b>   | 15 HP                                |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>  | 0 W                                  |
| <b>HEAT DISSIPATION CAPACITY PDISS</b>                     | 0 W                                  |
| <b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>   | 1.8 W                                |
| <b>NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)</b> | 0                                    |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY</b>              | 1                                    |

|   |   |
|---|---|
| <b>CLOSED CONTACTS)</b>                                     |   |
| <b>RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)</b>         | 80 kA   |
| <b>OVERVOLTAGE CATEGORY</b>                                 | III   |
| <b>CONTROL CIRCUIT RELIABILITY</b>                          | 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)   |
| <b>DEGREE OF PROTECTION (FRONT SIDE)</b>                    | IP65  |
| <b>NUMBER OF POLES</b>                                      | 4   |
| <b>MOUNTING METHOD</b>                                      | Rear mounting   |
| <b>DEGREE OF PROTECTION</b>                                 | NEMA 12   |
| <b>SUITABLE FOR</b>   | Branch circuits, suitable as motor disconnect, (UL/CSA)   |
| <b>LOCKING FACILITY</b>                                     | Lockable in the 0 (Off) position  |
| <b>FUNCTIONS</b>  | STOP function<br>Interlockable  |
| <b>NUMBER OF SWITCHES</b>                                   | 1   |
| <b>SAFE ISOLATION</b>                                       | 440 V AC, Between the contacts, According to EN 61140   |
| <b>SCREW SIZE</b>   | M4, Terminal screw  |
| <b>SHOCK RESISTANCE</b>                                     | 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms   |
| <b>LIFESPAN, MECHANICAL</b>                                 | 300,000 Operations  |
| <b>LOAD RATING</b>  | 2 x I <sub>e</sub> (with intermittent operation class 12, 25 % duty factor)<br>1.3 x I <sub>e</sub> (with intermittent operation class 12, 60 % duty factor)<br>1.6 x I <sub>e</sub> (with intermittent operation class 12, 40 % duty factor) |
| <b>SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)</b> | 10A, IU, (UL/CSA)   |
| <b>SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)</b>  | A600 (UL/CSA)<br>P600 (UL/CSA)  |
| <b>TERMINAL CAPACITY</b>                                    | 2 x (1.5 - 6) mm <sup>2</sup> , solid or stranded<br>14 - 8 AWG, solid or flexible with ferrule<br>1 x (1 - 4) mm <sup>2</sup> , flexible   |

|  |  |
|--|--|
|  | with ferrules to DIN 46228<br>2 x (1 - 4) mm <sup>2</sup> , flexible<br>with ferrules to DIN 46228<br>1 x (1.5 - 6) mm <sup>2</sup> , solid or<br>stranded |
| <b>SWITCHING CAPACITY<br/>(MAIN CONTACTS,<br/>GENERAL USE)</b>                   | 30 A, Rated uninterrupted<br>current max. (UL/CSA)   |
| <b>SAFETY PARAMETER (EN<br/>ISO 13849-1)</b>                                     | B10d values as per EN ISO<br>13849-1, table C.1  |
| <b>NUMBER OF AUXILIARY<br/>CONTACTS (NORMALLY<br/>OPEN CONTACTS)</b>             | 1  |
| <b>NUMBER OF CONTACTS<br/>IN SERIES AT DC-23A, 120<br/>V</b>                     | 3  |
| <b>NUMBER OF CONTACTS<br/>IN SERIES AT DC-23A, 24 V</b>                          | 1  |
| <b>NUMBER OF CONTACTS<br/>IN SERIES AT DC-23A, 48 V</b>                          | 2  |
| <b>NUMBER OF CONTACTS<br/>IN SERIES AT DC-23A, 60 V</b>                          | 2  |
| <b>RATED BREAKING<br/>CAPACITY AT 220/230 V<br/>(COS PHI TO IEC 60947-3)</b>     | 260 A  |
| <b>RATED BREAKING<br/>CAPACITY AT 400/415 V<br/>(COS PHI TO IEC 60947-3)</b>     | 300 A  |
| <b>RATED BREAKING<br/>CAPACITY AT 500 V (COS<br/>PHI TO IEC 60947-3)</b>         | 290 A  |
| <b>RATED BREAKING<br/>CAPACITY AT 660/690 V<br/>(COS PHI TO IEC 60947-3)</b>     | 250 A  |
| <b>RATED MAKING<br/>CAPACITY UP TO 690 V<br/>(COS PHI TO IEC/EN<br/>60947-3)</b> | 320 A  |
| <b>RATED OPERATING<br/>VOLTAGE (UE) - MAX</b>                                    | 690 V  |
| <b>RATED OPERATING<br/>VOLTAGE (UE) - MIN</b>                                    | 690 V  |
| <b>RATED OPERATIONAL<br/>VOLTAGE (UE) AT AC -<br/>MAX</b>                        | 690 V  |
| <b>SHORT-CIRCUIT CURRENT<br/>RATING (BASIC RATING)</b>                           | 5 kA, SCCR (UL/CSA)<br>110A, max. Fuse, SCCR<br>(UL/CSA)   |
| <b>SHORT-CIRCUIT CURRENT<br/>RATING (HIGH FAULT)</b>                             | 50 A, Class J, max. Fuse,<br>SCCR (UL/CSA)<br>10 kA, SCCR (UL/CSA)   |
| <b>SHORT-CIRCUIT</b>   | 50 A gG/gL, Fuse, Contacts   |

| <b>PROTECTION RATING</b>  |        |
|---|--------|
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-21, 440 V</b>                         | 32 A   |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-23A, 230 V</b>                        | 32 A   |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-23A, 400 V, 415 V</b>                 | 32 A   |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-23A, 500 V</b>                        | 30 A   |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-23A, 690 V</b>                        | 19.8 A |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V</b>            | 26.4 A |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V</b>            | 26.4 A |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 500 V</b>                          | 23.4 A |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 660 V, 690 V</b>                   | 14.7 A |
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-1, LOAD-BREAK SWITCHES L/R = 1 MS</b> | 32 A   |
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-23A, 120 V</b>                        | 12 A   |
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-23A, 24 V</b>                         | 25 A   |
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-23A, 48 V</b>                         | 25 A   |
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-23A, 60 V</b>                         | 25 A   |
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>          | 32 A   |
| <b>RATED OPERATIONAL POWER AT AC-23A, 220/230 V, 50 HZ</b>                    | 7.5 kW |
| <b>RATED OPERATIONAL POWER AT AC-23A, 400 V, 50 HZ</b>                        | 15 kW  |

---

**RATED OPERATIONAL  
POWER AT AC-23A, 500 V,  
50 HZ** 18.5 kW

---

**RATED OPERATIONAL  
POWER AT AC-23A, 690 V,  
50 HZ** 15 kW

---

**RATED OPERATIONAL  
POWER AT AC-3, 380/400  
V, 50 HZ** 13 kW

---

**RATED OPERATIONAL  
POWER AT AC-3, 415 V, 50  
HZ** 13 kW

---

**RATED OPERATIONAL  
POWER AT AC-3, 690 V, 50  
HZ** 15 kW

---

**HOUSING COLOR** Black

---

**HOUSING MATERIAL** Plastic

---

## Resources

**BROCHURES** [Brochure - T Rotary Cam switch and P Switch-disconnector](#)

---

**CATALOGS** [P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN](#)

---

**DECLARATIONS OF CONFORMITY** [eaton-main-switch-declaration-of-conformity-uk251289en.pdf](#)

[eaton-main-switch-declaration-of-conformity-eu250806en.pdf](#)

---

**DRAWINGS** [eaton-rotary-switches-padlock-t0-main-switch-dimensions.eps](#)

[eaton-rotary-switches-mounting-p1-main-switch-dimensions-002.eps](#)

[eaton-general-mounting-p1-main-switch-symbol-002.eps](#)

[eaton-rotary-switches-mounting-p1-main-switch-3d-drawing-002.eps](#)

[eaton-rotary-switches-t0-main-switch-symbol.eps](#)

---

**ECAD MODEL** [ETN.064978.edz](#)

---

**INSTALLATION INSTRUCTIONS** [eaton-switch-disconnector-p1-rear-mounting-il03802004z.pdf](#)

---

**INSTALLATION VIDEOS** [Eaton's P Switch-disconnectors used in a factory](#)

---

**MCAD MODEL** [eaton-p1\\_v\\_svb\\_n\\_hi11-3d-model.stp](#)

[eaton-main-switch-mcad-drawings-p1-v-svb-n-hi11.dwg](#)

---

**PRODUCT NOTIFICATIONS** [MZ008005ZU\\_Orderform\\_Customized\\_Switch.pdf](#)

[MZ008006ZU\\_Orderform\\_Customized\\_Switch.pdf](#)

---

**SPECIFICATIONS** [Eaton Specification Sheet - 064978](#)

---

AND  
DATASHEETS

WIRING [eaton-rotary-switches-main-switch-p1-main-](#)  
DIAGRAMS [switch-wiring-diagram.eps](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

