



Features

• OPTIX RECESSED 600x600 3L 4000K ALU SSC is a high efficacy low glare luminaire for office and education applications. Ceiling recessed 600x600 mm. Aluminised plastic extra low glare optics in 3 lines configuration. White RAL9016 fixture body. SylSmart Standalone capable. 4000K Neutral White LED, CRI>80, chromaticity tolerance of 3-step MacAdam ellipse. Luminous flux 3600lm. Power consumption 25.5W. Luminaire efficacy 141lm/W. Lifespan: 48,500 hours L90B10. UGR<16, Luminance at 65°<200 Cd/m2, IK07, IP20. Photobiological safety risk group 0. Electrical protection Class I. Glow wire test 850°C.


Product Overview

Product name	OPTIX RECESSED 600x600 3L 4000K ALU SSC
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
General application	Education, Office
ETIM Class	EC002892
Fixture luminous flux (lm)	3600
Luminaire efficacy (lm/W)	141
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 16
Photobiological Risk Group	RG0
Total power consumption (W)	25.5

OPTIX RECESSED 600x600 3L 4000K ALU SSC 2023612

Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9016
IP rating	IP20
IK rating	IK07
Product EAN number	5025768236121
Warranty	5 years
Dimming method	SylSmart SSC

Photometry




Concord

OPTIX RECESSED 600x600 3L 4000K ALU SSC

2023612

Technical drawings



Data table

GENERAL DATA

Product name	OPTIX RECESSED 600x600 3L 4000K ALU SSC
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
General application	Education, Office
Operating temperature range (°C)	10°C...+25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	3600
Luminaire efficacy (lm/W)	141

OPTIX RECESSED 600x600 3L 4000K ALU SSC 2023612

Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Distribution type	Symmetric
Glare control	< 16
Photobiological Risk Group	RG0

ELECTRICAL DATA

Total power consumption (W)	25.5
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.98
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	9
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	SylSmart SSC
Drive current (mA)	175
Inrush Current (A)	29
Inrush Duration (µs)	180
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 13A C Breaker	28
Max. products per 16A C Breaker	36
Max. products per 20A C Breaker	45
Max. products per 10A B Breaker	13
Max. products per 13A B Breaker	17
Max. products per 16A B Breaker	22
Max. products per 20A B Breaker	27

OPTIX RECESSED 600x600 3L 4000K ALU SSC 2023612

Connectable conductor cross section - Min (mm ²)	2.5
---	-----

Connectable conductor cross section - Max (mm ²)	2.5
---	-----

LIFETIME DATA

Lifespan L70 B50	120000
------------------	--------

Lifespan L80 B20	107500
------------------	--------

Lifespan L90 B10	48500
------------------	-------

PHYSICAL DATA

Housing colour	RAL9016
----------------	---------

IP rating	IP20
-----------	------

IK rating	IK07
-----------	------

Diffuser finish	Matt/satinized
-----------------	----------------

Diffuser material	PC Polycarbonate
-------------------	------------------

Nominal Product Length (mm)	596
-----------------------------	-----

Nominal Product Width (mm)	596
----------------------------	-----

Nominal Product Height (mm)	38
-----------------------------	----

Weight (kg)	5.0
-------------	-----

PACKAGING

Product EAN number	5025768236121
--------------------	---------------

Packaging single length / height (cm)	62.0
---------------------------------------	------

Packaging single width (cm)	6.5
-----------------------------	-----

Packaging single depth (cm)	65.0
-----------------------------	------

DUN14 (inner)	05025768236121
---------------	----------------

Units per outer package	1
-------------------------	---

Packaging outer length / height (cm)	62.0
--------------------------------------	------

Packaging outer width (cm)	6.5
----------------------------	-----

Packaging outer depth (cm)	65.0
----------------------------	------

SAFETY DATA

Concord

OPTIX RECESSED 600x600 3L 4000K ALU SSC 2023612

Glow Wire Test (°C)	850
Optimal operating condition (°C)	10-25
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No