

## CU-REGS-24V: Lcd standard Thermostat 24V



## Commercial information

LCD standard thermostat

| Basic unit dimensions |          |  |
|-----------------------|----------|--|
| Height                | 31 mm    |  |
| Length                | 86 mm    |  |
| Width                 | 86 mm    |  |
| Net weight            | 0.105 kg |  |

Certificates

**Applications** 

Heating, Cooling, Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Utility



## **Technical characteristics**

| rechnical characterist                                 | ICS                        |  |
|--|----------------------------|--|
| Regulation type on/off                                 | ×                          | Measuring range                        |
| Regulation type modulating                             | ✓                          | Number of heater outputs               |
| Communications protocol                                | Brand-dependent            | Number of cooler outputs               |
| Type of power supply                                   | 24 V                       | Differential value                     |
| Connection   | 3-/4-wire                  | Number of switching programmes         |
| With receiver  | ×                          | Max. contact voltage                   |
| External sensor  | ×                          | Max. contact load                      |
| With thermal feedback                                  | ×                          | Width                                  |
| Control characteristic                                 | Other                      | Depth                                  |
| Suitable for heating                                   | ✓                          | Height                                 |
| Suitable for heating                                   | ✓                          | Standby power consumption (solstandby) |
| Suitable for cooling                                   | ✓                          |  |
| Adjustable differential                                | ✓                          |  |
| Selector switch for heating and heating with hot water | ×                          |  |
| Sensor/feeler type                                     | Resistance sensor          |  |
| Temperature readable                                   | ✓                          |  |
| Relative humidity (RH) readable                        | ×                          |  |
| With display   | ✓                          |  |
| Type of clock  | Week clock                 |  |
| Clock model  | Digital                    |  |
| Overtime switch  | ×                          |  |
| Optimisation   | ×                          |  |
| With tap water circuit                                 | ×                          |  |
| Operation  | Button                     |  |
| Weather-dependent control system                       | ×                          |  |
| Contact type   | Normally open contact (NO) |  |
| Degree of protection (IP)                              | IP20                       |  |
| Degree of protection (NEMA)                            | 2                          |  |
| Explosion-proof  | ✓                          |  |
| Colour   | White                      |  |
| Compatible with Apple HomeKit                          | ×                          |  |
| Compatible with Google<br>Assistant                    | ×                          |  |
| Compatible with Amazon Alexa                           | ×                          |  |
| IFTTT support available                                | ×                          |  |
| • •  |                            |  |



0|40 Degrees celsius

-2|2 Kelvin

24 Volt

1 Ampere 86 Millimetre 86 Millimetre 31 Millimetre

2 Watt