


VEK-060502-Z: Manifold 1" with "3/4" male threaded outlets for eurocone, 1" 2x3/4" EK



Commercial information

Brass distributor 1" without vent opening with number of euro cone connections

Basic unit dimensions

| | |
|------------|----------|
| Height | 58 mm |
| Length | 103 mm |
| Width | 38 mm |
| Net weight | 0.529 kg |

Certificates

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

| | | | |
|------------------------------------|--|--------------------------------------|--------------------|
| Suitable for tap water | ✓ | Number of branches | 2 |
| Suitable for central heating water | ✓ | Number of branching directions | 1 |
| Suitable for cooling water | ✓ | Distance between offset | 50 Millimetre |
| Suitable for compressed air | ✗ | Max. medium temperature (continuous) | 95 Degrees celsius |
| Suitable for glycol | ✓ | Width | 38 Millimetre |
| Mounting method | Surface mounting | Height | 58 Millimetre |
| Model | Distributor/collector | Length distributor | 103 Millimetre |
| Material | Brass | | |
| Surface protection | Untreated | | |
| Shape | Throughflow with straight branches | | |
| Nominal diameter connection 2 | 1 inch (25) | | |
| Connection 2 | Internal thread cylindrical BSPP-G (ISO 228-1) | | |
| Nominal diameter branches | 3/4 inch (20) | | |
| Connection branches | Euroconus according to EN 16313 | | |
| Deviant distance between branches | ✗ | | |
| With filling/drain tap | ✗ | | |
| System specific | ✓ | | |
| With shut-off valve | ✗ | | |
| With de-aeration | ✗ | | |
| With wall-mounting bracket | ✗ | | |
| With mounting material | ✗ | | |
| With legs | ✗ | | |
| With insulation | ✗ | | |
| KOMO certified | ✗ | | |
| Type approval according to BBR/EKS | ✗ | | |