





Color: ■ black



Dimensions in mm

Physical data	
Width	35 mm / 1.378 inches
Height	16.9 mm / 0.665 inches
Depth	52.8 mm / 2.079 inches

Mechanical data	
Mounting type	Screw mount
Suitable	for 5-wire connectors (4 mm²)

Material data	
Note (material data)	Information on material specifications can be found here
Color	black
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.147 MJ
Weight	4.9 g

Commercial data	
PU (SPU)	50 (10) pcs
Packaging type	Box
Country of origin	CN
GTIN	4055143640848
Customs tariff number	39269097900



Product Classification	
UNSPSC	39121421
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 10.0	EC002848
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance
221-505/000-004

↓

Documentation				
Bid Text				
221-505/000-004	19.02.2019	xml 2.71 KB	↓	
221-505/000-004	04.01.2018	doc 24.00 KB	↓	

CAD/CAE-Data

CAD data

2D/3D Models
221-505/000-004

↓

CAE data

ZUKEN Portal
221-505/000-004

↓

- 1 Compatible Products
- 1.1 Optional Accessories
- 1.1.1 Marking
- 1.1.1.1 Marking strip




Item No.: 210-833
Marking strips; 25 m on roll; 6 mm wide;
plain; Self-adhesive; white

Installation Notes



Inserting a connector into the mounting carrier.



Removing a connector from the mounting carrier.

Conductor termination



Inserting a conductor.



Horizontal screw mounting



Vertical screw mounting



Horizontal mounting via snap-in foot



Vertical mounting via snap-in foot

Strain relief




Use a cable tie to secure the conductors to the strain relief plate.



The strain relief plate can be removed.

Testing



Testing a connector mounted on the carrier via test slot.

Application



Connecting a light to the mains.

Marking



Labeling the mounting carrier.