

VSK-161616: Extension or body for manifold, 3 SK connections Ø16



Commercial information

Synthetic manifold or extension with SK connectors Ø16

Basic unit dimensions

Height	30 mm
Length	174 mm
Width	66 mm
Net weight	0.151 kg

Certificates

QB (CSTBat), ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, KOMO, STF, GOST-R, TSU, EMI

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Suitable for tap water	✓	Outer pipe diameter connection 1	16 Millimetre
Suitable for central heating water	✓	Outer pipe diameter connection 2	0 Millimetre
Suitable for cooling water	✓	Number of branches	3
Suitable for compressed air	✗	Number of branching directions	1
Suitable for glycol	✓	Distance between offset	50 Millimetre
Mounting method	Surface mounting	Max. medium temperature (continuous)	70 Degrees celsius
Model	Distributor/collector	Width	66 Millimetre
Material	Plastic	Height	30 Millimetre
Material quality	Polyvinylidene fluoride (PVDF)	Length distributor	174 Millimetre
Surface protection	Untreated		
Shape	Throughflow with straight branches		
Connection 1	Insert (push-fitting)		
Nominal diameter connection 2	3/4 inch (20)		
Connection 2	External thread cylindrical BSPP-G (ISO 228-1)		
Nominal diameter branches	DN 15		
Connection branches	Other		
Deviant distance between branches	✗		
With filling/drain tap	✗		
System specific	✓		
With shut-off valve	✗		
With de-aeration	✗		
With wall-mounting bracket	✗		
With mounting material	✗		
With legs	✗		
With insulation	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		