




## VB050504-ROOD: Manifold 3/4" with ball valves - 4 EK-conections Red



### Commercial information

Brass Henco distributor 3/4" connection with ball valve and eurocone connections

- Universal eurocone connections
- Can be closed per group
- Short installation length
- Can be installed both horizontally and vertically as upside down

Available in a 3/4" and a 1" version

Available in blue and red.

Suitable for heating, air conditioning and sanitary installations.

Via configuration distributor possibility of parallel use of cold and/or hot circuits.

#### Basic unit dimensions

Height	70 mm
Length	195 mm
Width	50 mm
Net weight	0.763 kg

#### Certificates

#### Applications

Potable water, Heating, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

Suitable for tap water	✓	Number of branches	4
Suitable for central heating water	✓	Number of branching directions	1
Suitable for cooling water	✓	Distance between offset	50 Millimetre
Suitable for compressed air	✗	Max. medium temperature (continuous)	95 Degrees celsius
Suitable for glycol	✓	Width	50 Millimetre
Mounting method	Surface mounting	Height	70 Millimetre
Model	Distributor/collector	Length distributor	195 Millimetre
Material	Brass		
Surface protection	Untreated		
Shape	Throughflow with straight branches		
Nominal diameter connection 2	3/4 inch (20)		
Connection 2	Internal thread cylindrical BSPP-G (ISO 228-1)		
Nominal diameter branches	3/4 inch (20)		
Connection branches	Euroconus standardless		
Deviant distance between branches	✗		
With filling/drain tap	✗		
System specific	✓		
With shut-off valve	✓		
With de-aeration	✗		
With wall-mounting bracket	✗		
With mounting material	✗		
With legs	✗		
With insulation	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		