## **PRODUCT CARD**

16.8.2024



| Product code          | VB04-0044                     |                                  | STK-code    | 5201758 | EAN-code          | 6430051860409  |
|-----------------------|-------------------------------|----------------------------------|-------------|---------|-------------------|----------------|
| Product name          | Low Voltage Joint kit         | Al/Cu 4x16-50 mm <sup>2</sup>    |             |         | ETIM class        | EC001169       |
| Wires                 | Al/Cu 4x16-50 mm <sup>2</sup> |                                  |             |         |                   |                |
| Technical data        |                               |                                  |             |         |                   |                |
|                       |                               | -                                |             |         |                   |                |
|                       |                               | -                                |             |         |                   |                |
| Nominal voltage (IEC) |                               | 1000                             | V           |         |                   |                |
|                       |                               | -                                |             |         | OCOLANIS DESILENS |                |
|                       |                               | -                                |             |         | Eliner.           | And the second |
|                       |                               | -                                |             |         | 88.0              | -              |
|                       |                               | -                                |             |         |                   |                |
|                       |                               | •                                |             |         |                   |                |
|                       |                               |                                  |             |         | 11100             |                |
|                       |                               | •                                |             |         | 100               |                |
|                       |                               | •                                |             |         |                   |                |
|                       |                               | •                                |             |         |                   |                |
|                       |                               | •                                |             |         |                   |                |
|                       |                               | •                                |             |         |                   |                |
|                       |                               | •                                |             |         | $\epsilon$        | Palls          |
| Weight                |                               | 576                              | g           |         | • •               | KOHS           |
|                       |                               | •                                |             |         |                   |                |
| Standards             |                               | EN IEC 61238-1-1:2019            |             |         |                   |                |
| Color / Material      |                               | Tin plated Aluminium, Modified p | olyethylene |         |                   |                |
| Mounting / Connection |                               | Shear bolt                       |             |         |                   |                |

Kit can be used connecting 4-conductor <1 kV Voltage cables. Package includes four splice connectors, four inner heat shrink tubes for conductors, one outer heat shrink tube for cable, sandpaper and cleaning wipe. Connectors are pretreated with connection grease for the corrosion prevention. Installation is made with shear head screws.

## Drawing



| Package     |     |   |               |     |   |             |      |
|-------------|-----|---|---------------|-----|---|-------------|------|
| Package     | Bag | P | Pcs / Package |     | 1 | Weight [kg] | 0,58 |
|             |     |   |               |     |   |             |      |
| Length [mm] | 650 |   | Width [mm]    | 100 |   | Height [mm] | 70   |
|             |     |   |               |     |   |             |      |

## Ouneva Oy

Teollisuustie 21 FI-82730 Tuupovaara Finland www.ounevagroup.fi

www.ounevaproducts.fi