



Features

- SportsBay luminaire developed for sports halls with 18400lumens, 118W, 156lm/W, 4000K, CRI 80, wide beam 117°optic, SylSmart SSA dimmable without PIR motion detection, 3 step MacAdam ellipse, Class 1, 220-240V, IP20, IK10, lifespan 100Khrs L70B50, (LxWxH) 1500x320x66mm. Ball-impact-resistance according to VDE 0710-13.


Product Overview

Product name	Sportsbay 1500mm 18400lm 840 SSA01N
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
General application	Education, Logistics & Industry
ETIM Class	EC002892
Fixture luminous flux (lm)	18400
Luminaire efficacy (lm/W)	156
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	117
Glare control	< 24
Photobiological Risk Group	RG1
Total power consumption (W)	118
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
LED Flickering Rate	Ultra low (5% or less)


Sportsbay 1500mm 18400lm 840 SSA01N
0044067

Housing colour	RAL9016
IP rating	IP20
IK rating	IK10
Product EAN number	5410288440675
Warranty	5 years
Dimming method	SylSmart SSA

Photometry



Technical drawings



Data table

GENERAL DATA

Sportsbay 1500mm 18400lm 840 SSA01N 0044067

Product name	Sportsbay 1500mm 18400lm 840 SSA01N
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
General application	Education, Logistics & Industry
Operating temperature range (°C)	-20°C...+35°C
ETIM Class	EC002892
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	18400
Luminaire efficacy (lm/W)	156
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Luminous Intensity (cd)	6280
Beam Angle (°)	117
Distribution type	Symmetric
Glare control	< 24
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	118
Primary Supply/Product voltage - min (V)	198.0
Primary Supply/Product voltage - max (V)	264.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes

Sportsbay 1500mm 18400lm 840 SSA01N 0044067

Dimming method	SylSmart SSA
Drive current (mA)	350
Inrush Current (A)	27
Inrush Duration (µs)	200
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	10
Max. products per 13A C Breaker	14
Max. products per 16A C Breaker	17
Max. products per 20A C Breaker	22
Max. products per 10A B Breaker	6
Max. products per 13A B Breaker	8
Max. products per 16A B Breaker	10
Max. products per 20A B Breaker	13
Connectable conductor cross section - Min (mm²)	1.5
Connectable conductor cross section - Max (mm²)	2.5

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B50	81000
Lifespan L80 B20	76000

PHYSICAL DATA

Housing colour	RAL9016
IP rating	IP20
IK rating	IK10
IK rating of sensor	IK03
Diffuser finish	Other
Diffuser material	None
Nominal Product Length (mm)	1500



Sportsbay 1500mm 18400lm 840 SSA01N
0044067

Nominal Product Width (mm)	320
Nominal Product Height (mm)	66
Weight (kg)	11.9

PACKAGING

Product EAN number	5410288440675
Packaging single length / height (cm)	154.9
Packaging single width (cm)	34.9
Packaging single depth (cm)	7.11
DUN14 (inner)	05410288440675
Units per outer package	1
Packaging outer length / height (cm)	154.0
Packaging outer width (cm)	7.2
Packaging outer depth (cm)	34.0

SAFETY DATA

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-20-35
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No