

29P-2622: Press-fitt adapter to copper pipe 26x22 CW617N



Commercial information

Henco brass press fittings: the best solution for every situation.

29P Brass (CW617N) press fitting:

- Suitable for Henco multilayer pipes measuring 16 mm in diameter
- Body material: brass (CW617N), nickel-plated
- Connection 1: press fitting, 16/20/26/32 mm
- Connection 2: solder or compression fitting, 15/22/28 mm (copper)
- Press fitting material: stainless steel
- O-ring material: EPDM
- Suitable press profiles: TH/BE for pipes measuring 16 mm in diameter
- Suitable for drinking water and heating
- Fitted with leak detection (Leak Before Press)
- Extremely pressure and temperature resistant
- Fitted with a thrust washer to prevent electrolysis
- Press fitting comes with three viewing windows

Basic unit dimensions

| | |
|------------|----------|
| Net weight | 0.138 kg |
|------------|----------|

Certificates

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Utility, Shipbuilding, Industry, Energy/district heating

Technical characteristics

| | | | |
|-------------------------------|--------------------|----------------------------------|------------------------|
| Material connection 1 | Brass | Bend radius | 0 Millimetre |
| Material quality connection 1 | CuZn40Pb2 (CW617N) | Outer pipe diameter connection 1 | 26 Millimetre |
| Material connection 2 | Copper | Outer pipe diameter connection 2 | 22 Millimetre |
| Shape | Straight | Medium temperature (continuous) | -10 70 Degrees celsius |
| Reducing | ✘ | Max. operating pressure at 20 °C | 16 Bar |
| Eccentric | ✘ | Standard Dimension Ratio (SDR) | 0 |
| System specific | ✓ | | |
| Connection 1 | Press sleeve | | |
| Contour code connection 1 | TH | | |
| Connection 2 | Soldered end | | |
| Main colour fitting | Brass | | |
| Self-sealing | ✘ | | |
| With thermal insulation | ✘ | | |
| Ring stiffness class | Other | | |
| Capped | ✘ | | |
| With connection indicator | ✘ | | |
| With drain valve | ✘ | | |
| With de-aerator | ✘ | | |
| FM quality mark | ✘ | | |
| LPCB quality mark | ✘ | | |
| ULC quality mark | ✘ | | |
| UL quality mark | ✘ | | |
| DIN-CERTCO certificate | ✘ | | |
| VdS quality mark | ✘ | | |
| With approval for TÜV | ✘ | | |
| DVGW quality mark for gas | ✘ | | |
| DVGW quality mark for water | ✓ | | |
| KIWA certified | ✘ | | |
| Gastec QA mark | ✘ | | |