

Lok-it! HSD 300 W/80/P28

Lok-it! Metal Halide | High performance lamps with special twist and lock base for easy lamp replacement



Areas of application

- Concert Lighting
- Club & Disco
- Stage & Theatre
- Studio, TV, & Film
- Architecture & Architainment

Product features and benefits

- Compact design and short arc gap allows for smaller and brighter fixures
- Fast lamp replacement with one-touch rotate and lock base and socket design
- Robust design with eXtreme Seal (XS) technology, allowing up to 450°C at the pinch seal
- Consistent lumen output over the life of the lamp
- Improved ceramic base allows high voltage up to 35kV
- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency





Product datasheet

Technical data

General Product Information

| Product number (Americas) | 54382 | |
|---------------------------|-----------------------------------|--|
| Product name (Americas) | LOK-IT HSD 300/80/P28 10/CS 1/SKU | |
| Family brand | Lok-it! | |
| Global order reference | Lok-it! HSD 300 W/80/P28 | |


Electrical Data

| Nominal wattage | 300 W |
|-----------------|--------|
| Nominal voltage | 95.0 V |

Photometric Data

| Nominal luminous flux | 20500 lm | |
|---------------------------|----------|--|
| Color temperature | 8700 K | |
| Color rendering index Ra | >70 | |
| Light center length (LCL) | 67.0 mm | |

Physical Attributes & Dimensions



| Electrode gap (cold) | 5.0 mm |
|----------------------|----------|
| Lamp base | - |
| Diameter (in) | 0.906 in |
| Diameter | 23.0 mm |
| Length | 121.0 mm |
| Product weight | 140.00 g |

Operating Conditions

| Burning position | Other |
|------------------|-------|

Product datasheet

Lifetime Data

| Nominat uretime 2000 nr | Nominal lifetime | 2000 hr |
|-------------------------|------------------|---------|
|-------------------------|------------------|---------|

Environmental & Regulatory Information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | |
|---|------------------------------------|--|--|
| Primary article identifier | 4008321644831 | | |
| Declaration no. in SCIP database | No declarable substances contained | | |
| Candidate list substance 1 | No declarable substances contained | | |

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, Lok-it! lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-----------------------------|---------------------------------|--------------------------------------|----------------------|--------------|
| 4008321644831 | Lok-it! HSD 300 W/80/P28 | Shipping carton box 1 | 57 mm x 57 mm x 173 mm | 0.56 dm ³ | 172.00 g |
| 4008321644848 | Lok-it! HSD 300 W/80/P28 | | - x - x - | 7.01 dm³ | |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.