

Splashproof garden post with double socket outlet, side earthing and spike, black

761-36825

$\frac{h}{2} \times \frac{16 \text{ A}}{250 \text{ Vac}}$

CE

4 year warranty

The garden post includes two socket outlets (16 A/250 Vac) with side earthing, shutters and plug-in terminals. It has an IP55 protection degree and is equipped with a spike that needs to be driven directly into the earth. Its functional and beautiful design makes the garden post a perfect fit for outdoor areas, such as on terraces and in outdoor kitchens. Moreover, the entire unit is splashproof, which makes it extremely well-suited for use in damp areas and ammonia-rich environments.

- wire is fixed firmly due to the high-quality plug-in terminal with a long life span, tested according to the norm
- since the conductor release on the mechanisms is located at the front, the wiring cannot push on the release when you place it in the box

Faster and easier installation:

- all connections terminals are located at the top of the base:

Niko quality:

- long life span since the plug-in terminal stays within the limits of the norm during a temperature and power drop

Technical data

Splashproof garden post with double socket outlet, side earthing and spike, black.


Handmade product: small deviations in form may occur

- Function:
 - socket outlet
 - contact buses with a large contact surface that do not rest on the base in order to be connected
- Maximum MCB rating: 16 A (1.5 mm²) / 20 A (2.5 mm²) (limited by national installation rules)
- Number of mechanisms: 2
- Material finishing: stainless steel
- Colour: black
- Colour RAL (approximately): 9005



- Surface treatment: coloured in mass
- Type of inlet: one double M20 input with cable glands
- Terminal wire connection: plug-in terminals
- Type of inlet: one double M20 input with cable glands
- Chemical resistance: tested and approved for use in environments with ammonia levels up to 20 ppm
- Protection degree: IP55 for the combination of a socket outlet and a splashproof mounting box
- Impact resistance: the combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Dimensions (HxWxD): 347 mm x 83 mm x 68 mm
- Marking: CE

Dimensions



Wiring diagram

