



Color: ■ black

Locking system WINSTA® MINI

The locking system from the WINSTA® MINI product line guarantees you the greatest flexibility in electrical installation. An extensive range of accessories complements the WINSTA® product line from WAGO. WINSTA® MINI follows the trend towards miniaturisation. Our smallest pluggable connection system is very good for lights, for instance, since due to LED technology, these offer less and less space for the connection technology.

WINSTA® MINI solutions for your electrical installation – protected against mismatching and maintenance-free

The WINSTA® Pluggable Connection System is ideally tailored to the strict requirements of building installation. It makes electrical installation pluggable, and thus more efficient, even more reliable, and error-free. Use of this pre-assembled system decreases time spent on assembly and installation errors at the construction site. Choose durability and quality – with protection against mismatching from WAGO makes the installation of electrical components significantly easier.

- easy tool-free operation, a wide range of coding options
- fast, secure installation

Notes

General safety information

NOTICE: Observe installation and safety instructions!

- Nur von Elektrofachkraft oder einer für die Tätigkeit elektrisch unterwiesenen Person (EUP nach DIN VDE 0105-100) anzuwenden!
- Nicht unter Spannung/Last installieren!
- Nur für bestimmungsgemäßen Gebrauch einsetzen!
- Nationale Vorschriften/Normen/Richtlinien beachten!
- Technische Daten der Produkte beachten!
- Auf die richtige Polbelegung achten!
- Keine beschädigten/verschmutzten Komponenten verwenden!
- Leiterarten, -querschnitte, Abisolierlängen und Leitungsdurchmesser beachten!
- Leiter bis zum Anschlag einführen!
- Nur mit Verriegelungsklinke und Zugentlastung verwenden!
- Originalzubehör verwenden!

To be sold only with installation instructions!

Connection Data

Connection 1

Actuation type	Finger-operated lever
----------------	-----------------------

Physical data

Width	9 mm / 0.354 inches
Height	6.73 mm / 0.265 inches
Depth	26.23 mm / 1.033 inches

Mechanical data

Suitable	for flying leads; manually operated
----------	-------------------------------------

Material data

Note (material data)	Information on material specifications can be found here
Color	black
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.019 MJ
Weight	0.6 g

Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

PU (SPU)	100 (50) pcs
Packaging type	Box
Country of origin	DE
GTIN	4055143356930
Customs tariff number	85389099990

Product Classification

UNSPSC	39121703
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 9.0	EC002863
ETIM 10.0	EC002863
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

Approvals for marine applications



Approval	Standard	Certificate Name
LR Lloyds Register	EN 61535	LR23317167TA

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 890-101	↓

Documentation

Bid Text			
890-101	19.02.2019	xml 2.62 KB	↓
890-101	13.04.2017	doc 21.50 KB	↓

CAD/CAE-Data

CAD data	
2D/3D Models 890-101	↓

CAE data	
ZUKEN Portal 890-101	↓

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com