

# Threefold faceplate, vertical 71 mm centre distance, for three double switch functions, Niko Toggle alu grey brushed

155-57952

4 year warranty

The Niko Toggle threefold vertically oriented faceplate clicks onto three double switch functions that have been horizontally installed next to each other with a centre distance of 71 mm. The faceplate combines with any available Niko Toggle double switch function. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is made of brushed aluminium. The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA). The upper frame is 6 mm thick and the lower frame 2 mm.

Niko recommends a design combination with a finishing set in the following colour: alu grey.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)

## Technical data

Threefold faceplate, vertical 71 mm centre distance, for three double switch functions, Niko Toggle alu grey brushed.

- Threefold faceplate for three switches.
- Colour: alu grey (approximately NCS S 2002 - G, RAL 000 80 00)
- Recommended colour central plate: alu grey
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of brushed aluminium.
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA).
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Lighting element
  - the faceplate is fitted with a light guide
  - the light guide is made of a translucent plastic
  - the light guide transports the light from the optional LED to the lever
  - please note that the faceplate should not be mounted upside down to ensure that the optional LED fits nicely with the light guide
- Centre-to-centre distance: 71 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
  - self-extinguishing: complies with a filament test of 650°C
  - halogen-free



**niko**

- Protection degree: The combination of a mechanism, a central plate and a faceplate has a protection degree of IP20D
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 225 x 83 x 13 mm
- Dimensions visible (HxWxD): 225 x 83 mm
- Marking: CE

