



Color: ■ white

#### Locking system WINSTA® MINI

When using the locking system from the WINSTA® MINI product line, error-free installation is guaranteed. You can rely on the quality of WINSTA® components from WAGO for your electrical installation accessories too. WINSTA® MINI satisfies the demand for miniaturisation. Our smallest pluggable connection system is primarily suited for lights, for instance, since due to LED technology, these offer less and less space for the connection technology.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

WINSTA® is the pluggable connection system that is perfectly tailored to the strict requirements of electrical installation. It ensures fast, secure and, above all, error-free installation of components and cables. Now you can also cut installation costs without compromising safety and quality: with protection against mismatching reduces the need for servicing and prevents unnecessary downtime.

- consistent IP40 protection
- rapid, structured electrical installation

#### Notes

General safety information

#### NOTICE: Observe installation and safety instructions!

- Nur von Elektrofachkraft oder einer für die Tätigkeit elektrisch unterwiesenen Person (EUP nach DIN VDE 0105-100) anzuwenden!
- Nicht unter Spannung/Last installieren!
- Nur für bestimmungsgemäßen Gebrauch einsetzen!
- Nationale Vorschriften/Normen/Richtlinien beachten!
- Technische Daten der Produkte beachten!
- Auf die richtige Polbelegung achten!
- Keine beschädigten/verschmutzten Komponenten verwenden!
- Leiterarten, -querschnitte, Abisolierlängen und Leitungsdurchmesser beachten!
- Leiter bis zum Anschlag einführen!
- Nur mit Verriegelungsklinke und Zugentlastung verwenden!
- Originalzubehör verwenden!

**To be sold only with installation instructions!**

## Connection Data

### Connection 1

Actuation type	Finger-operated lever
----------------	-----------------------

## Physical data

Width	9 mm / 0.354 inches
Height	6.73 mm / 0.265 inches
Depth	26.23 mm / 1.033 inches

## Mechanical data

Suitable	for flying leads; manually operated
----------	-------------------------------------

## Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	white
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.018 MJ
Weight	0.6 g

## Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

## Commercial data

PU (SPU)	100 (50) pcs
Packaging type	Box
Country of origin	DE
GTIN	4055143356923
Customs tariff number	85389099990

## Product Classification

UNSPSC	39121702
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 9.0	EC002863
ETIM 10.0	EC002863
ECCN	NO US CLASSIFICATION

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Approvals / Certificates**

Approvals for marine applications



Approval	Standard	Certificate Name
LR Lloyds Register	EN 61535	LR23317167TA

**Downloads**

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 890-121	<a href="#">↓</a>
--	-------------------

**Documentation**

Bid Text

890-121	13.04.2017	doc 21.50 KB	<a href="#">↓</a>
890-121	19.02.2019	xml 2.62 KB	<a href="#">↓</a>

**CAD/CAE-Data**

CAD data

2D/3D Models 890-121	<a href="#">↓</a>
----------------------	-------------------

CAE data

ZUKEN Portal 890-121	<a href="#">↓</a>
----------------------	-------------------