
Walraven RapidStrut® Wall Plate (Hinged) (BUP1000)

(H1225)

hinged base foot to connect fixing rails with an angle





Features & benefits

- wall plate with hinging U-profile
- for wall fixing of rail
- rail can be fixed with slot downwards or sideways
- also used to strengthen constructions with Walraven RapidStrut® 41x41
- material: steel 1.0332
- product is part of the Walraven Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227



| Product Number | For Rail Type | Total Width x Total Height x Total Length | Width | Height | Length | Heart To Heart Distance | Anchoring Slot | Fixing Hole | Material Thickness | Material Thick- ness 2 | Maximum Allowed Load Faz |
|------------------|-----------------------------------|---|-------|--------|--------|-------------------------------|-------------------|----------------|-----------------------|------------------------------|--------------------------------|
| Reference lette | | WxHxL | w | h | I | k | AS | FH | MT | MT2 | Fa,z |
| Unit description | | mm x mm x mm | mm | mm | mm | mm | mm | mm | mm | mm | N |
| 66588814 | 41x21, 41x41, 41x51, 41x62, 41x82 | 82.2 x 156.5 x 120 | 59 | 55 | 41 | 70.6 | 25x12.2 | 13.8 | 4.00 | 4 | 2,500 |