

## BAP-FFV2605EK: Inox ball valve with handle, press x ek Ø26 x 3/4"



### Commercial information

With the BAP-FFV valve assortment, Henco offers stainless steel valves that guarantee an extra-long life, regardless of water hardness. They are also the right solution for "heavy duty" environments such as hospitals, farms, car washes, laboratories, etc. Also suitable for osmosis and demineralised water.

This stainless steel valve offers the user a unique range of benefits:

- Connections: press x eurocone
- KIWA and DVGW certified
- Available in diameters from 16 to 26 mm
- With removable levers
- Equipped with Leak Before Press functionality
- With color indication for water type

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 83 mm    |
| Length     | 119 mm   |
| Width      | 32 mm    |
| Net weight | 0.267 kg |

#### Certificates

KIWA SE, KIWA

#### Applications

Potable water, Heating, Compressed air, Sanitary

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

|                                     |  |  |                                 |                        |
|-------------------------------------|--|--|---------------------------------|------------------------|
| Housing material                    | Stainless steel                                |  | Medium temperature (continuous) | -35 70 Degrees celsius |
| Material quality                    | Stainless steel 316 L (1.4404)                 |  | Length of connection 1          | 44.2 Millimetre        |
| Surface protection housing          | None   |  | Working length connection 1     | 30.5 Millimetre        |
| Material ball                       | Stainless steel                                |  | Length of connection 2          | 67.8 Millimetre        |
| Surface protection ball             | None   |  | Working length connection 2     | 37 Millimetre          |
| Material spindle                    | Stainless steel                                |  | Handgrip length                 | 12.2 Millimetre        |
| Material primary spindle seal       | Other  |  |                                 |                        |
| Material secondary spindle seal     | Other  |  |                                 |                        |
| Nominal diameter connection 1       | 3/4 inch (20)                                  |  |                                 |                        |
| Connection 1                        | External thread cylindrical BSPP-G (ISO 228-1) |  |                                 |                        |
| With coupling connection 1          | ✗  |  |                                 |                        |
| Nominal diameter connection 2       | DN 15  |  |                                 |                        |
| Connection 2                        | Press sleeve                                   |  |                                 |                        |
| With coupling connection 2          | ✗  |  |                                 |                        |
| Contour code connection 2           | TH/BE  |  |                                 |                        |
| Article compression class           | PN 16  |  |                                 |                        |
| With drain valve                    | ✗  |  |                                 |                        |
| With drain possibility (connection) | ✗  |  |                                 |                        |
| With filter                         | ✗  |  |                                 |                        |
| With thermometer                    | ✗  |  |                                 |                        |
| Model                               | Straight                                       |  |                                 |                        |
| With insulation shell               | ✗  |  |                                 |                        |
| FM quality mark                     | ✗  |  |                                 |                        |
| UL quality mark                     | ✗  |  |                                 |                        |
| ULC quality mark                    | ✗  |  |                                 |                        |
| LPCB quality mark                   | ✗  |  |                                 |                        |
| Fire-safe                           | ✗  |  |                                 |                        |
| Medically clean                     | ✗  |  |                                 |                        |
| Grease-free                         | ✗  |  |                                 |                        |
| Operation                           | Lever handle                                   |  |                                 |                        |
| Full bore                           | ✓  |  |                                 |                        |
| VdS quality mark                    | ✗  |  |                                 |                        |
| DVGW quality mark for gas           | ✗  |  |                                 |                        |
| DVGW quality mark for water         | ✗  |  |                                 |                        |
| KIWA certified                      | ✓  |  |                                 |                        |
| Type approval according to BBR/EKS  | ✗  |  |                                 |                        |