

COLOSSAL 400mm 940 PRISM DIR WHITE DALI

Item No: 2071128


Concord



400mm diameter circular architectural luminaire, can be surface mounted or suspended. Powder coated aluminium housing (RAL9016) with PMMA prismatic diffuser. Direct light distribution, 1650lm luminous flux, 16W system power, 103lm/W luminaire efficacy. DALI dimmable. Colour rendering index Ra >90, 4000K Neutral White LED, chromaticity tolerance of 3-step MacAdam ellipse. IP40, IK03. 350mA drive current. UGR≤19. Electrical protection Class1, 220-240V. Reported lifetime 66k hours L90B10.

Technical Assets


Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	E(0°) [lx]	E(C0) [lx]	3004	814
0.5	1.04	E(0°) 48.2°	E(C0) 48.2°	774	129
1.0	2.09	E(0°) 48.2°	E(C0) 48.2°	944	97
1.5	3.13	E(0°) 48.2°	E(C0) 48.2°	195	52
2.0	4.17	E(0°) 48.2°	E(C0) 48.2°	124	21
2.5	5.21	E(0°) 48.2°	E(C0) 48.2°	88	14
3.0	6.26	E(0°) 48.2°	E(C0) 48.2°		

Distance [m] Cone diameter [m] Illuminance [lx]
C0 - C180 (Half beam angle: 92.4°)



COLOSSAL 400mm 940 PRISM DIR
WHITE DALI

Item No: 2071128

Concord

General data

Product name	COLOSSAL 400mm 940 PRISM DIR WHITE DALI
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling surface mounting, Suspended
General application	Hospitality, Office
Operating temperature range (°C)	10°C...+25°C
ETIM Class	EC002892
Warranty	5 years

Optical data

Fixture luminous flux (lm)	1650
Luminaire efficacy (lm/W)	103
Correlated colour temperature (k)	4000
Colour Code	940
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	16
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI-2
Drive current (mA)	350
Inrush Current (A)	20
Inrush Duration (µs)	200
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	31
Max. products per 13A C Breaker	39
Max. products per 16A C Breaker	51
Max. products per 20A C Breaker	62
Max. products per 10A B Breaker	18
Max. products per 16A B Breaker	30
Max. products per 20A B Breaker	37
Connectable conductor cross section - Min (mm²)	1.5
Connectable conductor cross section - Max (mm²)	2.5

Lifetime data

Lifespan L70 B50	170000
Lifespan L80 B20	145000
Lifespan L90 B10	66000

COLOSSAL 400mm 940 PRISM DIR WHITE DALI

Item No: 2071128

Concord

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP40/20
IK rating	IK07
Diffuser finish	Prismatic
Diffuser material	PMMA Acrylic
Nominal Product Height (mm)	93
Nominal Product Diameter (mm)	400
Weight (kg)	6.5

Packaging

Product EAN number	5025768711284
Packaging single length / height (cm)	14.0
Packaging single width (cm)	47.0
Packaging single depth (cm)	47.0
DUN14 (inner)	05025768711284
Units per outer package	1
Packaging outer length / height (cm)	14.0
Packaging outer width (cm)	47.0
Packaging outer depth (cm)	47.0

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	10-25